

H&H SH Single Axle Flatbed Trailer MODEL Specifications



Model	SH 5X10F FLATBED	SH 5X12F FLATBED	SH 5X14F FLATBED	SH 5.5X10F FLATBED	SH 5.5X12F FLATBED	SH 5.5X14F FLATBED	SH 8X10F FLATBED	SH 8X12F FLATBED	SH 8X14F FLATBED	SH 8.5X10F FLATBED	SH 8.5X12F FLATBED	SH 8.5X14F FLATBED
Overall Width	80 1/2"	80 1/2"	80 1/2"	86 1/2"	86 1/2"	86 1/2"	94 1/2"	94 1/2"	94 1/2"	102"	102"	102"
Overall Length	14'-6"	16'-6"	18'-6"	14'-6"	16'-6"	18'-6"	14'-6"	16'-6"	18'-6"	14'-6"	16'-6"	18'-6"
(Ramp Up) Overall Height	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"
Deck Height	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"
Deck Length	10'-0"	12'-0"	14'-0"	10'-0"	12'-0"	14'-0"	10'-0"	12'-0"	14'-0"	10'-0"	12'-0"	14'-0"
Width Between Fenders	60 1/4"	60 1/4"	60 1/4"	66 1/4"	66 1/4"	66 1/4"	76 1/4"	76 1/4"	76 1/4"	82 1/4"	82 1/4"	82 1/4"
*Curb Weight (lbs)	930	990	1050	990	1050	1110	1050	1130	1210	1130	1210	1290
*Gross Capacity (GVWR)	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990
*Payload Capacity (lbs)	2060	2000	1940	2000	1940	1880	1940	1860	1780	1860	1780	1700
Tongue Construction	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel
Tongue Length	3'-0"	3'-0"	3'-0"	4'-0"	4'-0"	4'-0"	4'-0"	4'-0"	4'-0"	4'-0"	4'-0"	4'-0"
Coupler	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame
Coupler Height	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"
Safety Chains & Hooks	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Jack	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel
Frame Construction	4"x3" angle	4"x3" angle	4"x3" angle	4"x3" angle	4"x3" angle	4"x3" angle	4"x3" angle	4"x3" angle	4"x3" angle	4"x3" angle	4"x3" angle	4"x3" angle
Crossmembers	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle
Ramp Height	50"	50"	50"	50"	50"	50"	50"	50"	50"	50"	50"	50"
Ramp Width	58"	58"	58"	64"	64"	64"	74"	74"	74"	80"	80"	80"
Ramp Load Capacity (lbs)*	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000
Axle (lbs)	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990
Axle Type	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler
Brakes	-	-	-	-	-	-	-	-	-	-	-	-
Breakaway Kit w/ Battery	-	-	-	-	-	-	-	-	-	-	-	-
Tire Size	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75
Tire Load Range	C	C	C	C	C	C	C	C	C	C	C	C
Tire Ply	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial
Rim Size	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"
Bolt Pattern	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5
Trailer Plug	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong
Wiring in Conduit	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED

*All weights are approximate and are based on the standard model (adding options may increase the empty weight). Trailer weights may vary. Weights are calculated in pounds (lbs).