

# H&H LSA Aluminum Low Side Single Axle Utility Trailer MODEL Specifications



Model	LSA 56 X8F SA	LSA 56 X10F SA	LSA 56 X12F SA	LSA 56 X14F SA	LSA 62 X10F SA	LSA 62 X12F SA	LSA 62 X14F SA	LSA 72 X10F SA	LSA 72 X12F SA	LSA 72 X14F SA	LSA 78 X10F SA	LSA 78 X12F SA	LSA 78 X14F SA
Overall Length	11'-9"	13'-8 1/4"	15'-6"	17'-4 1/4"	13'-8 1/4"	15'-6"	17'-4 1/4"	13'-8 1/4"	15'-6"	17'-4 1/4"	13'-8 1/4"	15'-6"	17'-4 1/4"
Overall Width (Ramp Folded)	80"	80"	80"	80"	86"	86"	86"	96"	96"	96"	102"	102"	102"
Overall Height	45 1/2"	45 1/2"	45 1/2"	45 1/2"	45 1/2"	45 1/2"	45 1/2"	45 1/2"	45 1/2"	45 1/2"	45 1/2"	45 1/2"	45 1/2"
Deck Height	16-1/2"	16-1/2"	16-1/2"	16-1/2"	16-1/2"	16-1/2"	16-1/2"	16-1/2"	16-1/2"	16-1/2"	16-1/2"	16-1/2"	16-1/2"
Deck Length	8'-0"	10'-0"	12'-0"	14'-0"	10'-0"	12'-0"	14'-0"	10'-0"	12'-0"	14'-0"	10'-0"	12'-0"	14'-0"
Deck Width	56"	56"	56"	56"	62"	62"	62"	72"	72"	72"	78"	78"	78"
Deck Width (Between Fenders)	60"	60"	60"	60"	66"	66"	66"	76"	76"	76"	82"	82"	82"
*Curb Weight (lbs)	580	620	670	720	670	750	820	680	740	790	720	770	820
*Gross Capacity (GWVR)	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990
*Payload Capacity (lbs)	2410	2370	2320	2270	2320	2240	2170	2310	2250	2200	2270	2220	2170
Tongue Construction	4" Stacked Tube A-frame	4" Stacked Tube A-frame	4" Stacked Tube A-frame	4" Stacked Tube A-frame	4" Stacked Tube A-frame	4" Stacked Tube A-frame	4" Stacked Tube A-frame	4" Stacked Tube A-frame	4" Stacked Tube A-frame	4" Stacked Tube A-frame	4" Stacked Tube A-frame	4" Stacked Tube A-frame	4" Stacked Tube A-frame
Tongue Length	42"	42"	42"	42"	42"	42"	42"	42"	42"	42"	42"	42"	42"
Coupler	2" straight	2" straight	2" straight	2" straight	2" straight	2" straight	2" straight	2" straight	2" straight	2" straight	2" straight	2" straight	2" straight
Coupler Height	18"	18"	18"	18"	18"	18"	18"	18"	18"	18"	18"	18"	18"
Safety Chains & Hooks	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Jack	2K swivel	2K swivel	2K swivel	2K swivel	2K swivel	2K swivel	2K swivel	2K swivel	2K swivel	2K swivel	2K swivel	2K swivel	2K swivel
Frame Construction	6" extruded	6" extruded	6" extruded	6" extruded	6" extruded	6" extruded	6" extruded	6" extruded	6" extruded	6" extruded	6" extruded	6" extruded	6" extruded
Crossmembers	none	none	none	none	none	none	none	none	none	none	none	none	none
Ramp Height (unfolded)	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"
Ramp Width	52 1/2"	52 1/2"	52 1/2"	52 1/2"	58 1/2"	58 1/2"	58 1/2"	68 1/2"	68 1/2"	68 1/2"	74 1/2"	74 1/2"	74 1/2"
Ramp Load Capacity (lbs)	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
Axle (lbs)	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990
Axle Type	Torsion idler	Torsion idler	Torsion idler	Torsion idler	Torsion idler	Torsion idler	Torsion idler	Torsion idler	Torsion idler	Torsion idler	Torsion idler	Torsion idler	Torsion idler
Brakes	-	-	-	-	-	-	-	-	-	-	-	-	-
Breakaway Kit w/ Battery	-	-	-	-	-	-	-	-	-	-	-	-	-
Tire Size	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75
Tire Load Range	C	C	C	C	C	C	C	C	C	C	C	C	C
Tire Ply	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial
Rim Size	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"
Bolt Pattern	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5
Trailer Plug	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED

\*All weights are approximate and are based on the standard model (adding options may increase the empty weight). Trailer weights may vary. Weights are calculated in pounds (lbs).