

H&H RSA Aluminum Rail Sided Tandem Axle Utility Trailer MODEL Specifications



Model	TRSA8 UT 12 RS	TRSA8 UT 14 RS	TRSA8 UT 16 RS	TRSA8 UT 18 RS	TRSA8 UT 20 RS	TRSA8.5 UT 12 RS	TRSA8.5 UT 14 RS	TRSA8.5 UT 16 RS	TRSA8.5 UT 18 RS	TRSA8.5 UT 20 RS
Overall Length	16'-4"	18'-4"	20'-4"	22'-4"	24'-4"	16'-9"	18'-9"	20'-9"	22'-9"	24'-9"
Overall Width	97 3/4"	97 3/4"	97 3/4"	97 3/4"	97 3/4"	102"	102"	102"	102"	102"
(Ramp Up) Overall Height	74 1/2"	74 1/2"	74 1/2"	74 1/2"	74 1/2"	74 1/2"	74 1/2"	74 1/2"	74 1/2"	74 1/2"
Deck Height	18 1/2"	18 1/2"	18 1/2"	18 1/2"	18 1/2"	18 1/2"	18 1/2"	18 1/2"	18 1/2"	18 1/2"
Deck Length	12'-0"	14'-0"	16'-0"	18'-0"	20'-0"	12'-0"	14'-0"	16'-0"	18'-0"	20'-0"
Deck Width (Between Fenders)	76 1/4"	76 1/4"	76 1/4"	76 1/4"	76 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"
*Curb Weight (lbs)	1260	1355	1420	1530	1660	1390	1485	1550	1640	1800
*Gross Capacity (GWVR)	7000	7000	7000	7000	7000	7000	7000	7000	7000	7000
*Payload Capacity (lbs)	5740	5645	5580	5470	5340	5610	5515	5450	5360	5200
Tongue Construction	5" channel angle brace	5" channel angle brace	5" channel angle brace	5" channel angle brace	5" channel angle brace	5" channel angle brace	5" channel angle brace	5" channel angle brace	5" channel angle brace	5" channel angle brace
Tongue Length	4'-0"	4'-0"	4'-0"	4'-0"	4'-0"	4'-5"	4'-5"	4'-5"	4'-5"	4'-5"
Coupler	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame
Coupler Height	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"
Safety Chains & Hooks	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Jack	5K set-back	5K set-back	5K set-back	5K set-back	5K set-back	5K set-back	5K set-back	5K set-back	5K set-back	5K set-back
Frame Construction	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle
Crossmembers	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle
Ramp Height	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"
Ramp Width	73"	73"	73"	73"	73"	79"	79"	79"	79"	79"
Ramp Load Capacity (lbs)	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
Axle (lbs)	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500
Axle Type	Leaf spring brake	Leaf spring brake	Leaf spring brake	Leaf spring brake	Leaf spring brake	Leaf spring brake	Leaf spring brake	Leaf spring brake	Leaf spring brake	Leaf spring brake
Brakes	4-wheel electric	4-wheel electric	4-wheel electric	4-wheel electric	4-wheel electric	4-wheel electric	4-wheel electric	4-wheel electric	4-wheel electric	4-wheel electric
Breakaway Kit w/ Battery	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Tire Size	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75
Tire Load Range	C	C	C	C	C	C	C	C	C	C
Tire Ply	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial
Rim Size	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"
Bolt Pattern	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5
Trailer Plug	7-way	7-way	7-way	7-way	7-way	7-way	7-way	7-way	7-way	7-way
Wiring in Conduit	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED

**All weights are approximate and are based on the standard model (adding options may increase the empty weight). Trailer weights may vary. Weights are calculated in pounds (lbs).*