

H&H MXA Manual Tilt Aluminum SpeedLoader Model Specifications



Model	H8218MXA-070	H8220MXA-070	H8222MXA-100	H8224MXA-100	H8218MXLA-070	H8220MXLA-070	H8222MXLA-100	H8224MXLA-100
Overall Length	23'-4"	25'-4"	27'-4"	29'-4"	23'-4"	25'-4"	27'-4"	29'-4"
Overall Width	102"	102"	102"	102"	102"	102"	102"	102"
Overall Height	31 1/2"	31 1/2"	33 1/2"	33 1/2"	28 1/2"	28 1/2"	33 1/2"	33 1/2"
Deck Height	24"	24"	26"	26"	20 1/2"	20 1/2"	22 1/2"	22 1/2"
Deck Length	18'-2"	20'-2"	22'-2"	24'-2"	18'-2"	20'-2"	22'-2"	24'-2"
Deck Width Between Fenders	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"	79 1/4"	79 1/4"
*Curb Weight (lbs)	1590	1670	2170	2270	1630	1710	2210	2310
*Gross Capacity (GVWR)	7000	7000	9900	9900	7000	7000	9900	9900
*Payload Capacity (lbs)	5410	5330	7730	7630	5370	5290	7690	7590
Degree of Slope	14	12	11	9	11	9	8	6
Tongue Construction	6" channel	6" channel	6" channel	6" channel	6" channel	6" channel	6" channel	6" channel
Tongue Length	62"	62"	62"	62"	62"	62"	62"	62"
Coupler	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame
Coupler Height	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"
Safety Chains & Hooks	yes	yes	yes	yes	yes	yes	yes	yes
Jack	7K drop leg	7K drop leg	7K drop leg	7K drop leg	7K drop leg	7K drop leg	7K drop leg	7K drop leg
Frame	6" channel	6" channel	8" channel	8" channel	6" channel	6" channel	8" channel	8" channel
Crossmember	3" channel	3" channel	3" channel	3" channel	3" channel	3" channel	3" channel	3" channel
Ramp Style	-	-	-	-	-	-	-	-
Ramp Height	-	-	-	-	-	-	-	-
Ramp Width	-	-	-	-	-	-	-	-
Ramp Load Capacity (lbs.)	-	-	-	-	-	-	-	-
Axle (lbs.)	(2) 3500	(2) 3500	(2) 5200	(2) 5200	(2) 3500	(2) 3500	(2) 5200	(2) 5200
Axle Type	Leaf spring brake	Leaf spring brake	Leaf spring brake	Leaf spring brake	Drop spring brake	Drop spring brake	Drop spring brake	Drop spring brake
Brakes	yes	yes	yes	yes	yes	yes	yes	yes
Breakaway Kit w/ Battery	yes	yes	yes	yes	yes	yes	yes	yes
Tire Size	ST205/75	ST205/75	ST225/75	ST225/75	ST205/75	ST205/75	ST225/75	ST225/75
Tire Load Range	C	C	C	C	C	C	C	C
Tire Ply	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial
Rim Size	15"	15"	15"	15"	15"	15"	15"	15"
Bolt Pattern	5 on 4.5	5 on 4.5	6 on 5.5	6 on 5.5	5 on 4.5	5 on 4.5	6 on 5.5	6 on 5.5
Trailer Plug	7-prong	7-prong	7-prong	7-prong	7-prong	7-prong	7-prong	7-prong
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED	LED

**All weights are approximate and are based on the standard model (adding options may increase the empty weight).
Trailer weights may vary. Weights are calculated in pounds (lbs).*

H&H EXA Electric Tilt Aluminum SpeedLoader Model Specifications



Model	H8218EXA-070	H8220EXA-070	H8222EXA-100	H8224EXA-100	H8218EXLA-070	H8220EXLA-070	H8222EXLA-100	H8224EXLA-100
Overall Length	23'-4"	25'-4"	27'-4"	29'-4"	23'-4"	25'-4"	27'-4"	29'-4"
Overall Width	102"	102"	102"	102"	102"	102"	102"	102"
Overall Height	31 1/2"	31 1/2"	33 1/2"	33 1/2"	28 1/2"	28 1/2"	33 1/2"	33 1/2"
Deck Height	24"	24"	26"	26"	20 1/2"	20 1/2"	22 1/2"	22 1/2"
Deck Length	18'-2"	20'-2"	22'-2"	24'-2"	18'-2"	20'-2"	22'-2"	24'-2"
Deck Width Between Fenders	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"	79 1/4"	79 1/4"
*Curb Weight (lbs)	1670	1750	2250	2350	1650	1730	2330	2430
*Gross Capacity (GVWR)	7000	7000	9900	9900	7000	7000	9900	9900
*Payload Capacity (lbs)	5330	5250	7650	7550	5350	5270	7570	7470
Degree of Slope	14	12	11	9	11	9	8	6
Tongue Construction	6" channel	6" channel	6" channel	6" channel	6" channel	6" channel	6" channel	6" channel
Tongue Length	62"	62"	62"	62"	62"	62"	62"	62"
Coupler	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame
Coupler Height	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"
Safety Chains & Hooks	yes	yes	yes	yes	yes	yes	yes	yes
Jack	7K drop leg	7K drop leg	7K drop leg	7K drop leg	7K drop leg	7K drop leg	7K drop leg	7K drop leg
Frame	6" channel	6" channel	8" channel	8" channel	6" channel	6" channel	8" channel	8" channel
Crossmember	3" channel	3" channel	3" channel	3" channel	3" channel	3" channel	3" channel	3" channel
Ramp Style	-	-	-	-	-	-	-	-
Ramp Height	-	-	-	-	-	-	-	-
Ramp Width	-	-	-	-	-	-	-	-
Ramp Load Capacity (lbs.)	-	-	-	-	-	-	-	-
Axle (lbs.)	(2) 3500	(2) 3500	(2) 5200	(2) 5200	(2) 3500	(2) 3500	(2) 5200	(2) 5200
Axle Type	Leaf spring brake	Leaf spring brake	Leaf spring brake	Leaf spring brake	Leaf spring brake	Drop spring brake	Drop spring brake	Drop spring brake
Brakes	yes	yes	yes	yes	yes	yes	yes	yes
Breakaway Kit w/ Battery	yes	yes	yes	yes	yes	yes	yes	yes
Tire Size	ST205/75	ST205/75	ST225/75	ST225/75	ST205/75	ST205/75	ST225/75	ST225/75
Tire Load Range	C	C	C	C	C	C	C	C
Tire Ply	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial
Rim Size	15"	15"	15"	15"	15"	15"	15"	15"
Bolt Pattern	5 on 4.5	5 on 4.5	6 on 5.5	6 on 5.5	5 on 4.5	5 on 4.5	6 on 5.5	6 on 5.5
Trailer Plug	7-prong	7-prong	7-prong	7-prong	7-prong	7-prong	7-prong	7-prong
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED	LED

**All weights are approximate and are based on the standard model (adding options may increase the empty weight). Trailer weights may vary. Weights are calculated in pounds (lbs).*