

H&H SS Solid Side Single Axle Trailer Model Specifications



Model	SS 5X8F SS	SS 5X10F SS	SS 5X12F SS	SS 5X14F SS	SS 5.5X8F SS	SS 5.5X10F SS	SS 5.5X12F SS	SS 5.5X14F SS	SS 8X10F SS	SS 8X12F SS	SS 8X14F SS	SS 8.5X10F SS	SS 8.5X12F SS	SS 8.5X14F SS
Overall Length	12'-6"	14'-6"	16'-6"	18'-6"	12'-6"	14'-6"	16'-6"	18'-6"	14'-6"	16'-6"	18'-6"	14'-6"	16'-6"	18'-6"
Overall Width	80 1/2"	80 1/2"	80 1/2"	80 1/2"	86 1/2"	86 1/2"	86 1/2"	86 1/2"	94 1/2"	94 1/2"	94 1/2"	102"	102"	102"
(Ramp Up) Overall Height	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"
Deck Height	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"
Deck Length	8'-0"	10'-0"	12'-0"	14'-0"	8'-0"	10'-0"	12'-0"	14'-0"	10'-0"	12'-0"	14'-0"	10'-0"	12'-0"	14'-0"
Deck Width Between Fenders	60 1/4"	60 1/4"	60 1/4"	60 1/4"	66 1/4"	66 1/4"	66 1/4"	66 1/4"	76 1/4"	76 1/4"	76 1/4"	82 1/4"	82 1/4"	82 1/4"
*Curb Weight (lbs)	830	870	970	1050	860	910	1030	1110	1030	1150	1210	1080	1170	1250
Gross Capacity (GVWR)	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990
*Payload Capacity	2160	2120	2020	1940	2130	2080	1960	1880	1960	1840	1780	1910	1820	1740
Tongue Construction	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel
Tongue Length	3'-1"	3'-1"	3'-1"	3'-1"	3'-9"	3'-9"	3'-9"	3'-9"	3'-9"	3'-9"	3'-9"	3'-9"	3'-9"	3'-9"
Coupler	2"	2"	2"	2"	2"	2"	2"	2"	2"	2"	2"	2"	2"	2"
Coupler Height	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"
Safety Chains & Hooks	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Frame	12ga steel 2"x2" angle	12ga steel 2"x2" angle	12ga steel 2"x2" angle	12ga steel 2"x2" angle	12ga steel 2"x2" angle	12ga steel 2"x2" angle	12ga steel 2"x2" angle	12ga steel 2"x2" angle	12ga steel 2"x2" angle	12ga steel 2"x2" angle	12ga steel 2"x2" angle	12ga steel 2"x2" angle	12ga steel 2"x2" angle	12ga steel 2"x2" angle
Crossmember	12ga steel 2"x2" angle	12ga steel 2"x2" angle	12ga steel 2"x2" angle	12ga steel 2"x2" angle	12ga steel 2"x2" angle	12ga steel 2"x2" angle	12ga steel 2"x2" angle	12ga steel 2"x2" angle	12ga steel 2"x2" angle	12ga steel 2"x2" angle	12ga steel 2"x2" angle	12ga steel 2"x2" angle	12ga steel 2"x2" angle	12ga steel 2"x2" angle
Ramp Height	50"	50"	50"	50"	50"	50"	50"	50"	50"	50"	50"	50"	50"	50"
Ramp Width	58"	58"	58"	58"	64"	64"	64"	64"	74"	74"	74"	80"	80"	80"
Ramp Load Capacity (lbs)*	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000
Axle (lbs)	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990
Axle Type	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler
Brakes	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Breakaway Kit w/ Battery	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Tire Size	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75
Tire Rating	C	C	C	C	C	C	C	C	C	C	C	C	C	C
Tire Ply	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial
Rim Size	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"
Bolt Pattern	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5
Trailer Plug	4-way	4-way	4-way	4-way	4-way	4-way	4-way	4-way	4-way	4-way	4-way	4-way	4-way	4-way
Wiring in Conduit	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED

*All weights are approximate and are based on the standard model (adding options may increase the empty weight). Trailer weights may vary. Weights are calculated in pounds (lbs).