

H&H RSA Aluminum Rail Sided Single Axle Utility Trailer MODEL Specifications



Model	RSA 5X8F RS	RSA 5X10F RS	RSA 5X12F RS	RSA 5X14F RS	RSA 5.5X8F RS	RSA 5.5X10F RS	RSA 5.5X12F RS	RSA 5.5X14F RS	RSA 8X10F RS	RSA 8X12F RS	RSA 8X14F RS	RSA 8.5X10F RS	RSA 8.5X12F RS	RSA 8.5X14F RS
Overall Length	11'-10"	13'-10"	15'-10"	17'-10"	11'-10"	13'-9"	15'-9"	17'-9"	14'-4"	16'-4"	18'-4"	14'-9"	16'-9"	18'-9"
Overall Width	78 1/4"	78 1/4"	78 1/4"	78 1/4"	84 1/4"	84 1/4"	84 1/4"	84 1/4"	94 1/4"	94 1/4"	94 1/4"	100 1/4"	100 1/4"	100 1/4"
(Ramp Up) Overall Height	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"
Deck Height	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"
Deck Length	8'-0"	10'-0"	12'-0"	14'-0"	8'-0"	10'-0"	12'-0"	14'-0"	10'-0"	12'-0"	14'-0"	10'-0"	12'-0"	14'-0"
Deck Width (Between Fenders)	60 1/4"	60 1/4"	60 1/4"	60 1/4"	66 1/4"	66 1/4"	66 1/4"	66 1/4"	76 1/4"	76 1/4"	76 1/4"	82 1/4"	82 1/4"	82 1/4"
*Curb Weight (lbs)	650	690	750	810	790	810	890	970	830	920	1010	890	980	1070
*Gross Capacity (GWVR)	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990
*Payload Capacity (lbs)	2340	2300	2240	2180	2200	2180	2100	2020	2160	2070	1980	2100	2010	1920
Tongue Construction	4" tube	4" tube	4" tube	4" tube	4" tube	4" tube	4" tube	4" tube	4" tube	4" tube	4" tube	4" tube	4" tube	4" tube
Tongue Length	42 1/2"	42 1/2"	42 1/2"	42 1/2"	41"	41"	41"	41"	48"	48"	48"	53"	53"	53"
Coupler	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame
Coupler Height	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"
Safety Chains & Hooks	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Jack	2K coupler	2K coupler	2K coupler	2K coupler	2K coupler	2K coupler	2K coupler	2K coupler	2K coupler	2K coupler	2K coupler	2K coupler	2K coupler	2K coupler
Frame Construction	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle
Crossmembers	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle	3"x2" angle
Ramp Height	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"
Ramp Width	57"	57"	57"	57"	63"	63"	63"	63"	73"	73"	73"	79"	79"	79"
Ramp Load Capacity (lbs)	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
Axle (lbs)	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990
Axle Type	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler
Brakes	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Breakaway Kit w/ Battery	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Tire Size	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75
Tire Load Range	C	C	C	C	C	C	C	C	C	C	C	C	C	C
Tire Ply	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial
Rim Size	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"
Bolt Pattern	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5
Trailer Plug	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED

*All weights are approximate and are based on the standard model (adding options may increase the empty weight). Trailer weights may vary. Weights are calculated in pounds (lbs).