H&H SSA Aluminum Solid Side Single Axle Utility Trailer MODEL Specifications

Model	SSA 5X8F SS	SSA 5X10F SS	SSA 5X12F SS	SSA 5X14F SS	SSA 5.5X8F SS	SSA 5.5X10F SS	SSA 5.5X12F SS	SSA 5.5X14F SS	SSA 8X10F SS	SSA 8X12F SS	SSA 8X14F SS	SSA 8.5X10F SS	SSA 8.5X12F SS	SSA 8.5X14F SS
Overall Length	11'-10"	13'-10"	15'-10"	17'-10"	11'-10"	13'-10"	15'-10"	17'-10"	14'-4"	16'-4"	18'-4"	14'-9"	16'-9"	18'-9"
Overall Width	78 1/4"	78 1/4"	78 1/4"	78 1/4"	85 1/4"	85 1/4"	85 1/4"	85 1/4"	94 1/4"	94 1/4"	94 1/4"	100 1/4"	100 1/4"	100 1/4"
(Ramp Up) Overall Height	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"
Deck Height	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"
Deck Length	8'-0"	10'-0"	12'-0"	14'-0"	8'-0"	10'-0"	12'-0"	14'-0"	10'-0"	12'-0"	14'-0"	10'-0"	12'-0"	14'-0"
ck Width Between Fenders	60 1/4"	60 1/4"	60 1/4"	60 1/4"	66 1/4"	66 1/4"	66 1/4"	66 1/4"	76 1/4"	76 1/4"	76 1/4"	82 1/4"	82 1/4"	82 1/4"
*Curb Weight (lbs)	740	830	920	1010	770	850	950	1060	880	1000	1090	960	1040	1120
*Gross Capacity (GWVR)	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990
*Payload Capacity (lbs)	2250	2160	2070	1980	2220	2140	2040	1930	2110	1990	1900	2030	1950	1870
Tongue Construction	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel
Tongue Length	3'-6"	3'-6"	3'-6"	3'-6"	3-5"	3-5"	3'-5"	3-5"	4'-0"	4'-0"	4'-0"	4'-5"	4'-5"	4'-5"
Coupler	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame
Coupler Height	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"
Safety Chains & Hooks	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Jack	2K swivel	2K swivel	2K swivel	2K swivel	2K swivel	2K swivel	2K swivel	2K swivel	2K swivel	2K swivel	2K swivel	2K swivel	2K swivel	2K swivel
Frame Construction	Formed 1/8" ATP	Formed 1/8" ATP	Formed 1/8" ATP	Formed 1/8" ATP	Formed 1/8" ATP	Formed 1/8" ATP	Formed 1/8" ATP	Formed 1/8" ATP	Formed 1/8" ATP	Formed 1/8" ATP	Formed 1/8" ATP	Formed 1/8" ATP	Formed 1/8" ATP	Formed 1/8" ATP
Crossmembers	3" channel	3" channel	3" channel	3" channel	3" channel	3" channel	3" channel	3" channel	3" channel	3" channel	3" channel	3" channel	3" channel	3" channel
Ramp Height	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"
Ramp Width	57"	57"	57"	57"	63"	63"	63"	63"	73"	73"	73"	79"	79"	79"
Ramp Load Capacity (lbs)	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
Axle (lbs)	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990
Axle Type	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler
Brakes	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Breakaway Kit w/ Battery	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Tire Size	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75
Tire Load Range	C	C	C	C	C	C	C	C	C	C	C	C	C	C
Tire Ply	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial
Rim Size	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"
Bolt Pattern	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5
Trailer Plug	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong
Wiring in Conduit	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED