

# H&H RS Rail Side Single Axle Trailer Model Specifications



Model	RS 5X8F RS	RS 5X10F RS	RS 5X12F RS	RS 5X14F RS	RS 5.5X8F RS	RS 5.5X10F RS	RS 5.5X12F RS	RS 5.5X14F RS	RS 8X10F RS	RS 8X12F RS	RS 8X14F RS	RS 8.5X10F RS	RS 8.5X12F RS	RS 8.5X14F RS
Overall Length	12'-6"	14'-6"	16'-6"	18'-6"	12'-6"	14'-6"	16'-6"	18'-6"	14'-6"	16'-6"	18'-6"	14'-6"	16'-6"	18'-6"
Overall Width	80 1/2"	80 1/2"	80 1/2"	80 1/2"	86 1/2"	86 1/2"	86 1/2"	86 1/2"	94 1/2"	94 1/2"	94 1/2"	102"	102"	102"
(Ramp Up) Overall Height	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"
Deck Height	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"
Deck Length	8'-0"	10'-0"	12'-0"	14'-0"	8'-0"	10'-0"	12'-0"	14'-0"	10'-0"	12'-0"	14'-0"	10'-0"	12'-0"	14'-0"
Deck Width Between Fenders	60 1/4"	60 1/4"	60 1/4"	60 1/4"	66 1/4"	66 1/4"	66 1/4"	66 1/4"	76 1/4"	76 1/4"	76 1/4"	82 1/4"	82 1/4"	82 1/4"
*Curb Weight (lbs)	750	810	870	930	790	890	990	1090	970	1050	1130	1010	1110	1210
Gross Capacity (GVWR)	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990
*Payload Capacity	2240	2180	2120	2060	2200	2100	2000	1900	2020	1940	1860	1980	1880	1780
Tongue Construction	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel
Tongue Length	3'	3'	3'	3'	4'	4'	4'	4'	4'	4'	4'	4'	4'	4'
Coupler	a-frame	a-frame	a-frame	a-frame	a-frame	a-frame	a-frame	a-frame	a-frame	a-frame	a-frame	a-frame	a-frame	a-frame
Coupler Height	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"
Safety Chains & Hooks	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Jack	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel
Frame	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle
Crossmember	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle
Ramp Height	50"	50"	50"	50"	50"	50"	50"	50"	50"	50"	50"	50"	50"	50"
Ramp Width	58"	58"	58"	58"	64"	64"	64"	64"	74"	74"	74"	80"	80"	80"
Ramp Load Capacity (lbs)*	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000
Axle (lbs)	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990
Axle Type	Spring Idler	Spring Idler	Spring Idler	Spring Idler	Spring Idler	Spring Idler	Spring Idler	Spring Idler	Spring Idler	Spring Idler	Spring Idler	Spring Idler	Spring Idler	Spring Idler
Brakes	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Breakaway Kit w/ Battery	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Tire Size	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75
Tire Rating	C	C	C	C	C	C	C	C	C	C	C	C	C	C
Tire Ply	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial
Rim Size	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"
Bolt Pattern	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5
Trailer Plug	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED

\*All weights are approximate and are based on the standard model (adding options may increase the empty weight). Trailer weights may vary. Weights are calculated in pounds (lbs).