

H&H SSUT Solid Side Tandem Axle Trailer Model Specifications



Model	STB UT 12 SS	STB UT 14 SS	STB UT 16 SS	STB UT 18 SS	STB UT 20 SS	STB .5UT 12 SS	STB .5UT 14 SS	STB .5UT 16 SS	STB .5UT 18 SS	STB .5UT 20 SS	STB .5UT 22 SS	STB .5UT 24 SS
Overall Length	16'-6"	18'-6"	20'-6"	22'-6"	24'-6"	16'-6"	18'-6"	20'-6"	22'-6"	24'-6"	26'-6"	28'-6"
Overall Width	94 1/2"	94 1/2"	94 1/2"	94 1/2"	94 1/2"	102"	102"	102"	102"	102"	102"	102"
Overall Height (Ramp Up)	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"
Deck Height	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"
Deck Length	12'-0"	14'-0"	16'-0"	18'-0"	20'-0"	12'-0"	14'-0"	16'-0"	18'-0"	20'-0"	22'-0"	24'-0"
Deck Width Between Fenders	76 1/4"	76 1/4"	76 1/4"	76 1/4"	76 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"
*Curb Weight (lbs)	1500	1590	1760	1860	1940	1520	1610	1790	1890	1970	2060	2155
*Gross Capacity (GVWR)	7000	7000	7000	7000	7000	7000	7000	7000	7000	7000	7000	7000
*Payload Capacity (lbs)	5500	5410	5240	5140	5060	5480	5390	5210	5110	5030	4940	4845
Tongue Construction	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel
Tongue Length	3'-4"	3'-4"	3'-4"	3'-4"	3'-4"	3'-4"	3'-4"	3'-4"	3'-4"	3'-4"	3'-4"	3'-4"
Coupler	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame
Coupler Height	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"
Safety Chains & Hooks	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Jack	set-back	set-back	set-back	set-back	set-back	set-back	set-back	set-back	set-back	set-back	set-back	set-back
Frame Construction	12ga steel 3"x2" angle	12ga steel 3"x2" angle	12ga steel 3"x2" angle	12ga steel 3"x2" angle	12ga steel 3"x2" angle	12ga steel 3"x2" angle	12ga steel 3"x2" angle	12ga steel 3"x2" angle	12ga steel 3"x2" angle	12ga steel 3"x2" angle	12ga steel 3"x2" angle	12ga steel 3"x2" angle
Crossmembers	angle	angle	angle	angle	angle	angle	angle	angle	angle	angle	angle	angle
Ramp Height	50"	50"	50"	50"	50"	50"	50"	50"	50"	50"	50"	50"
Ramp Width	74"	74"	74"	74"	74"	80"	80"	80"	80"	80"	80"	80"
Ramp Load Capacity (lbs)*	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000
Axle (lbs)	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500
Axle Type	Spring brake	Spring brake	Spring brake	Spring brake	Spring brake	Spring brake	Spring brake	Spring brake	Spring brake	Spring brake	Spring brake	Spring brake
Brakes	4-wheel electric	4-wheel electric	4-wheel electric	4-wheel electric	4-wheel electric	4-wheel electric	4-wheel electric	4-wheel electric	4-wheel electric	4-wheel electric	4-wheel electric	4-wheel electric
Breakaway Kit w/ Battery	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Tire Size	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75
Tire Load Range	C	C	C	C	C	C	C	C	C	C	C	C
Tire Ply	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial
Rim Size	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"
Bolt Pattern	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5
Trailer Plug	7-way	7-way	7-way	7-way	7-way	7-way	7-way	7-way	7-way	7-way	7-way	7-way
Wiring in Conduit	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED

*All weights are approximate and are based on the standard model (adding options may increase the empty weight). Trailer weights may vary. Weights are calculated in pounds (lbs).