

H&H WS Wood Side Single Axle Trailer Model Specifications



Model	WS 5X8F 24 RS	WS 5X10F 24 RS	WS 5X12F 24 RS	WS 5X14F 24 RS	WS 5.5X8F 24 RS	WS 5.5X10F 24 RS	WS 5.5X12F 24 RS	WS 5.5X14F 24 RS	WS 8X10F 24 RS	WS 8X12F 24 RS	WS 8X14F 24 RS	WS 8.5X10F 24 RS	WS 8.5X12F 24 RS	WS 8.5X14F 24 RS
Overall Length	12'-6"	14'-6"	16'-6"	18'-6"	12'-6"	14'-6"	16'-6"	18'-6"	14'-6"	16'-6"	18'-6"	14'-6"	16'-6"	18'-6"
Overall Width	80 1/2"	80 1/2"	80 1/2"	80 1/2"	86 1/2"	86 1/2"	86 1/2"	86 1/2"	94 1/2"	94 1/2"	94 1/2"	102"	102"	102"
Overall Height (Ramp Up)	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"
Deck Height	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"
Deck Length	8'-0"	10'-0"	12'-0"	14'-0"	8'-0"	10'-0"	12'-0"	14'-0"	10'-0"	12'-0"	14'-0"	10'-0"	12'-0"	14'-0"
Deck Width Between Fenders	58 1/2"	58 1/2"	58 1/2"	58 1/2"	64 1/2"	64 1/2"	64 1/2"	64 1/2"	74 1/2"	74 1/2"	74 1/2"	80 1/2"	80 1/2"	80 1/2"
*Curb Weight (lbs)	940	1050	1160	1270	980	1090	1200	1310	1140	1250	1360	1180	1290	1400
Gross Capacity (GVWR)	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990
*Payload Capacity	2050	1940	1830	1720	2010	1900	1790	1680	1850	1740	1630	1810	1700	1590
Tongue Construction	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel	4" channel
Tongue Length	3'	3'	3'	3'	4'	4'	4'	4'	4'	4'	4'	4'	4'	4'
Coupler	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame
Coupler Height	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"
Safety Chains & Hooks	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Jack	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel	2K Swivel
Frame	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle
Crossmember	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle
Ramp Height	50"	50"	50"	50"	50"	50"	50"	50"	50"	50"	50"	50"	50"	50"
Ramp Width	58"	58"	58"	58"	64"	64"	64"	64"	74"	74"	74"	80"	80"	80"
amp Load Capacity (lbs)*	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000
Axle (lbs)	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990	2990
Axle Type	Spring Idler	Spring Idler	Spring Idler	Spring Idler	Spring Idler	Spring Idler	Spring Idler	Spring Idler	Spring Idler	Spring Idler	Spring Idler	Spring Idler	Spring Idler	Spring Idler
Brakes	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Breakaway Kit w/ Battery	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Tire Size	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75
Tire Rating	C	C	C	C	C	C	C	C	C	C	C	C	C	C
Tire Ply	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial
Rim Size	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"
Bolt Pattern	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5
Trailer Plug	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED

*All weights are approximate and are based on the standard model (adding options may increase the empty weight). Trailer weights may vary. Weights are calculated in pounds (lbs).