

Model	SFTCA 6.10.72	SFTCA 6.12.72	SFTCA 6.14.72	SFTCA 7.10.72	SFTCA 7.12.72
Overall Length	15'-6"	17'-6"	19'-6"	15'-6"	17'-6"
Overall Width	93"	93"	93"	102"	102"
Overall Height	7'-8"	7'-8"	7'-8"	8'-0"	8'-0"
Interior Length	12'-2"	14'-2"	16'-2"	12'-2"	14'-2"
Interior Width	69"	69"	69"	81"	81"
Between Wheel Wells	-	-	-	-	-
Interior Height	73"	73"	73"	73"	73"
Deck Height	18"	18"	18"	18"	18"
Deck Box Length	9'-10"	11'-10"	13'-10"	9'-10"	11'-10"
*Empty Weight (lbs)	1310	1350	1390	1530	1590
*Gross Capacity (GVWR)	2990	2990	2990	2990	2990
*Payload Capacity (lbs)	1680	1640	1600	1460	1400
Tongue Construction	3" tube	3" tube	3" tube	4" tube	4" tube
Tongue Length	2'-10"	2'-10"	2'-10"	3'-2"	3'-2"
Coupler	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame
Coupler Height	17"	17"	17"	17"	17"
Jack	2K swivel	2K swivel	2K swivel	2K swivel	2K swivel
Crossmember Spacing	Formed channel 24" OC	Formed channel 24" OC	Formed channel 24" OC	Formed channel 24" OC	Formed channel 24" OC
Wall Uprights Spacing	24" OC	24" OC	24" OC	24" OC	24" OC
Roof Bow Spacing	24" OC	24" OC	24" OC	24" OC	24" OC
Exterior Sheeting	.024	.024	.024	.024	.024
Side Escape Door	yes	yes	yes	yes	yes
Side Escape Door Height	68"	68"	68"	68"	68"
Side Escape Door Width	32"	32"	32"	32"	32"
**Rear Door Type	Ramp	Ramp	Ramp	Ramp	Ramp
Rear Door Opening Height	70"	70"	70"	70"	70"
Rear Door Opening Width	66"	66"	66"	78"	78"
Ramp Load Capacity (lbs)	1000	1000	1000	1000	1000
Axles (lbs)	3500	3500	3500	3500	3500
Axle Type	Drop spring idler	Drop spring idler	Drop spring idler	Drop spring idler	Drop spring idler
Brakes	-	-	-	-	-
Breakaway Kit with Battery	-	-	-	-	-
Tire Size	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75
Tire Load Range	C	C	C	C	C
Tire Ply	Radial	Radial	Radial	Radial	Radial
Rim Size	15"	15"	15"	15"	15"
Bolt Pattern	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5
Brake Lights	LED	LED	LED	LED	LED
Clearance/Marker Lights	LED	LED	LED	LED	LED
Trailer Plug	4-prong	4-prong	4-prong	4-prong	4-prong