

H&H ATV Single Axle Utility Trailer MODEL Specifications



Model	SH 5 X12F 4-Wheeler	SH 8 X12F HEAVY 4-Wheeler	SH 8 X14F HEAVY 4-Wheeler	SH 8.5X12F HEAVY 4-Wheeler	SH 8.5X14F HEAVY 4-Wheeler
Overall Length	16'-6"	16'-6"	18'-6"	16'-6"	18'-6"
Overall Width	80 1/2"	94 1/2"	94 1/2"	102"	102"
(Ramp Up) Overall Height	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"
Deck Height	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"
Deck Length	12'-0"	12'-0"	14'-0"	12'-0"	14'-0"
Deck Width Between Fenders	60 1/4"	76 1/4"	76 1/4"	82 1/4"	82 1/4"
*Curb Weight (lbs)	1130	1230	1330	1390	1410
*Gross Capacity (GVWR)	2990	2990	2990	2990	2990
*Payload Capacity (lbs)	1860	1760	1660	1600	1580
Tongue Construction	4" channel	4" channel	4" channel	4" channel	4" channel
Tongue Length	3'-1"	3'-9"	3'-9"	3'-9"	3'-9"
Coupler	2" a-frame	2" a-frame	2" a-frame	2" a-frame	2" a-frame
Coupler Height	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"
Safety Chains & Hooks	yes	yes	yes	yes	yes
Jack	2K swivel	2K swivel	2K swivel	2K swivel	2K swivel
Frame Construction	3"x2" angle	4"x3" angle	4"x3" angle	4"x3" angle	4"x3" angle
Crossmembers	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle	2"x2" angle
Ramp Height	50"	50"	50"	50"	50"
Ramp Width	58"	74"	74"	80"	80"
Ramp Load Capacity (lbs)*	2000	2000	2000	2000	2000
Axle (lbs)	2990	2990	2990	2990	2990
Axle Type	Spring idler	Spring idler	Spring idler	Spring idler	Spring idler
Brakes	-	-	-	-	-
Breakaway Kit w/ Battery	-	-	-	-	-
Tire Size	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75
Tire Load Range	C	C	C	C	C
Tire Ply	Radial	Radial	Radial	Radial	Radial
Rim Size	15"	15"	15"	15"	15"
Bolt Pattern	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5
Trailer Plug	4-way	4-way	4-way	4-way	4-way
Wiring in Conduit	yes	yes	yes	yes	yes
Exterior Lighting	LED	LED	LED	LED	LED

*All weights are approximate and are based on the standard model (adding options may increase the empty weight). Trailer weights may vary. Weights are calculated in pounds (lbs).

