

H&H SSA Aluminum Solid Sided Tandem Axle Utility Trailer MODEL Specifications



Model	SSA8 UT 12 SS	SSA8 UT 14 SS	SSA8 UT 16 SS	SSA8 UT 18 SS	SSA8 UT 20 SS	SSA8 .5UT 12 SS	SSA8 .5UT 14 SS	SSA8 .5UT 16 SS	SSA8 .5UT 18 SS	SSA8 .5UT 20 SS
Overall Length	16'-4"	18'-4"	20'-4"	22'-4"	24'-4"	16'-9"	18'-9"	20'-9"	22'-9"	24'-9"
Overall Width	97 3/4"	97 3/4"	97 3/4"	97 3/4"	97 3/4"	102"	102"	102"	102"	102"
Overall Height (Ramp Up)	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"
Deck Height	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"
Deck Length	12'-0"	14'-0"	16'-0"	18'-0"	20'-0"	12'-0"	14'-0"	16'-0"	18'-0"	20'-0"
Deck Width (Between Fenders)	76 1/4"	76 1/4"	76 1/4"	76 1/4"	76 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"
*Curb Weight (lbs)	1370	1440	1510	1580	1650	1430	1510	1630	1720	1810
*Gross Capacity (GWVR)	7000	7000	7000	7000	7000	7000	7000	7000	7000	7000
*Payload Capacity (lbs)	5630	5560	5490	5420	5350	5570	5490	5370	5280	5190
Tongue Construction	5" channel angle brace	5" channel angle brace	5" channel angle brace	5" channel angle brace	5" channel angle brace	5" channel angle brace	5" channel angle brace	5" channel angle brace	5" channel angle brace	5" channel angle brace
Tongue Length	4'-0"	4'-0"	4'-0"	4'-0"	4'-0"	4'-5"	4'-5"	4'-5"	4'-5"	4'-5"
Coupler	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame	2 5/16" a-frame
Coupler Height	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"
Safety Chains & Hooks	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Jack	set-back	set-back	set-back	set-back	set-back	set-back	set-back	set-back	set-back	set-back
Frame Construction	Formed 1/8" ATP	Formed 1/8" ATP	Formed 1/8" ATP	Formed 1/8" ATP	Formed 1/8" ATP	Formed 1/8" ATP	Formed 1/8" ATP	Formed 1/8" ATP	Formed 1/8" ATP	Formed 1/8" ATP
Crossmembers	3" channel	3" channel	3" channel	3" channel	3" channel	3" channel	3" channel	3" channel	3" channel	3" channel
Ramp Height	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"
Ramp Width	73"	73"	73"	73"	73"	79"	79"	79"	79"	79"
Ramp Load Capacity (lbs)	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
Axle (lbs)	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500	(2) 3500
Axle Type	Spring brake	Spring brake	Spring brake	Spring brake	Spring brake	Spring brake	Spring brake	Spring brake	Spring brake	Spring brake
Brakes	4-wheel electric	4-wheel electric	4-wheel electric	4-wheel electric	4-wheel electric	4-wheel electric	4-wheel electric	4-wheel electric	4-wheel electric	4-wheel electric
Breakaway Kit w/ Battery	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Tire Size	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75
Tire Load Range	C	C	C	C	C	C	C	C	C	C
Tire Ply	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial
Rim Size	15"	15"	15"	15"	15"	15"	15"	15"	15"	15"
Bolt Pattern	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5
Trailer Plug	7-way	7-way	7-way	7-way	7-way	7-way	7-way	7-way	7-way	7-way
Wiring in Conduit	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED	LED	LED	LED

**All weights are approximate and are based on the standard model (adding options may increase the empty weight). Trailer weights may vary. Weights are calculated in pounds (lbs).*