



ALUMINUM RAIL SIDE UTILITY



FEATURES

- 3"x 2" Angle Aluminum Extrusion Frame
- Aluminum Extrusion Tube Upright Sides
- Aluminum Extrusion 2"x2" Tube Top Rail
- Aluminum Triple Tube Tongue
- Treated #1 Grade Wood Deck - front and rear end caps
- Radial Tires on 15" Aluminum Wheels
- A-Frame Posi-Lock Coupler
- Dual Safety Chain & Hooks - DOT Approved
- 1K Rated Swivel Jack with Caster Wheel (Single Axle)
- Set-Back Jack (Tandem Axle)
- Full DOT Compliant, LED Lighting
- Sealed Wiring Harness
- Aluminum Stake Pockets
- 54" Bi-Fold Gate (2200 lb Rated)

OPTIONS

- 2-5/16" Adjustable Height Coupler
- Extruded Aluminum Deck
- Full Enclosed Wiring
- Utility Stake Pockets
- Spare Tire
- Brake Axle
- Tongue Mounted Toolbox
- **Contact Your Local Dealer for More Options**





ALUMINUM RAIL SIDE UTILITY

Single Axle

Model Size	60" x 8'	60" x 10'	66" x 10'	66" x 12'	76" x 10'	76" x 12'	82" x 12'	82" x 14'
GAWR (lb/axle)	3500	3500	3500	3500	3500	3500	3500	3500
*Gross Capacity (GWVR)	2990	2990	2990	2990	2990	2990	2990	2990
*Curb Weight (lb)	650	690	810	890	830	920	980	1050
*Payload Capacity (lb)	2340	2300	2180	2100	2160	2070	2010	1940
Frame Construction	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle
Crossmembers	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle
Top Rail	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube
Uprights	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube
Tongue Construction	4" Tube	4" Tube	4" Tube	4" Tube	4" Tube	4" Tube	4" Tube	4" Tube
Tongue Length	42 1/2"	42 1/2"	41"	41"	48"	48"	53"	53"
Coupler	2" A-frame	2" A-frame	2" A-frame	2" A-frame	2" A-frame	2" A-frame	2" A-frame	2" A-frame
Coupler Height	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"
Safety Chains & Hooks	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Jack	1K Rated Swivel	1K Rated Swivel	1K Rated Swivel	1K Rated Swivel	1K Rated Swivel	1K Rated Swivel	1K Rated Swivel	1K Rated Swivel
Axle Type	Spring Idler	Spring Idler	Spring Idler	Spring Idler	Spring Idler	Spring Idler	Spring Idler	Spring Idler
Brakes	-	-	-	-	-	-	-	-
Breakaway Kit w/ Battery	-	-	-	-	-	-	-	-
Tire Size	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75
Tire Load Range	C	C	C	C	C	C	C	C
Tire Ply	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial
Rim Size	15"	15"	15"	15"	15"	15"	15"	15"
Bolt Pattern	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5
Trailer Plug	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong	4-prong
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED	LED
Decking	No. 1 Grade, Pressure Treated Pine	No. 1 Grade, Pressure Treated Pine	No. 1 Grade, Pressure Treated Pine	No. 1 Grade, Pressure Treated Pine	No. 1 Grade, Pressure Treated Pine	No. 1 Grade, Pressure Treated Pine	No. 1 Grade, Pressure Treated Pine	No. 1 Grade, Pressure Treated Pine
Ramp Height	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"
Ramp Width	57"	57"	63"	63"	73"	73"	79"	79"
Ramp Load Capacity (lb)	2200	2200	2200	2200	2200	2200	2200	2200
Overall Length	11'-10"	13'-10"	13'-9"	15'-9"	14'-4"	16'-4"	16'-9"	18'-9"
Overall Width	78 1/4"	78 1/4"	84 1/4"	84 1/4"	94 1/4"	94 1/4"	100 1/4"	100 1/4"
Overall Height	49"	49"	49"	49"	49"	49"	49"	49"
Deck Height	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"
Deck Length	8'-0"	10'-0"	10'-0"	12'-0"	10'-0"	12'-0"	12'-0"	14'-0"
Deck Width	60 1/4"	60 1/4"	66 1/4"	66 1/4"	76 1/4"	76 1/4"	82 1/4"	82 1/4"

Tandem Axle

Model Size	82" x 14' TA	82" x 16' TA	82" x 18' TA	82" x 20' TA
GAWR (lb/axle)	3500	3500	3500	3500
*Gross Capacity (GWVR)	7000	7000	7000	7000
*Curb Weight (lb)	1485	1550	1640	1800
*Payload Capacity (lb)	5515	5450	5360	5200
Frame Construction	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle
Crossmembers	3" Channel	3" Channel	3" Channel	3" Channel
Top Rail	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube
Uprights	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube
Tongue Construction	5" Tube Wrapped with Tube Cross Brace	5" Tube Wrapped with Tube Cross Brace	5" Tube Wrapped with Tube Cross Brace	5" Tube Wrapped with Tube Cross Brace
Tongue Length	53"	53"	53"	53"
Coupler	2-5/16" A-frame	2-5/16" A-frame	2-5/16" A-frame	2-5/16" A-frame
Coupler Height	14 1/2"	14 1/2"	14 1/2"	14 1/2"
Safety Chains & Hooks	Yes	Yes	Yes	Yes
Jack	2K Rated Set-back	2K Rated Set-back	2K Rated Set-back	2K Rated Set-back
Axle Type	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake
Brakes	4-wheel Electric	4-wheel Electric	4-wheel Electric	4-wheel Electric
Breakaway Kit w/ Battery	Yes	Yes	Yes	Yes
Tire Size	ST205/75	ST205/75	ST205/75	ST205/75
Tire Load Range	C	C	C	C
Tire Ply	Radial	Radial	Radial	Radial
Rim Size	15"	15"	15"	15"
Bolt Pattern	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5
Trailer Plug	7-way	7-way	7-way	7-way
Exterior Lighting	LED	LED	LED	LED
Decking	No. 1 Grade, Pressure Treated Pine	No. 1 Grade, Pressure Treated Pine	No. 1 Grade, Pressure Treated Pine	No. 1 Grade, Pressure Treated Pine
Ramp Height	54 1/2"	54 1/2"	54 1/2"	54 1/2"
Ramp Width	79"	79"	79"	79"
Ramp Load Capacity (lb)	2200	2200	2200	2200
Overall Length	18'-9"	20'-9"	22'-9"	24'-9"
Overall Width	102"	102"	102"	102"
Overall Height	49"	49"	49"	49"
Deck Height	18 1/2"	18 1/2"	18 1/2"	18 1/2"
Deck Length	14'-0"	16'-0"	18'-0"	20'-0"
Deck Width	82 1/4"	82 1/4"	82 1/4"	82 1/4"

