

Specification Page

INDUSTRIAL DUMP

DUMP TRAILERS





	83" x 12' (14K)	83" x 14' (14K)	83" x 16' (14K)	83" x 14' (16K)	83" x 16' (16K)
Model	H8312DBW-B-140	H8314DBW-B-140	H8316DBW-B-140	H8314DBW-B-160	H8316DBW-B-160
GAWR (lb./axle)	7000	7000	7000	8000	8000
GVWR (lb.)	14000	14000	14000	16000	16000
Curb Weight (lb.)	3880	4100	4550	4250	4700
Payload Capacity (lb.)	10120	9900	9450	11750	11300
Frame Construction	8" Channel				
Crossmembers	3" Channel, 16" OC				
Sides	24" Tall, 12-Gauge Steel	24" Tall, 12-Gauge Steel	24" Tall, 10-Gauge Steel	24" Tall, 12-Gauge Steel	24" Tall, 10-Gauge Steel
Tongue Construction	6" Channel				
Coupler	2 5/16" Adj. Height				
Coupler Height	12.5"-20.5"	12.5"-20.5"	12.5"-20.5"	12.5"-20.5"	12.5"-20.5"
Safety Chains	Yes	Yes	Yes	Yes	Yes
Jack	7K Rated Drop Leg	7K Rated Drop Leg	7K Rated Drop Leg	12K Rated Drop Leg	12K Rated Drop Leg
Axle Type	Leaf Spring Brake				
Brakes	4-Wheel Electric				
Breakaway Kit	Yes	Yes	Yes	Yes	Yes
Tires	ST235/80R16 'E'	ST235/80R16 'E'	ST235/80R16 'E'	ST215/75R17.5 'H'	ST215/75R17.5 'H'
Wheels	16", 8 on 6.5	16", 8 on 6.5	16", 8 on 6.5	17.5", 8 on 6.5	17.5", 8 on 6.5
Trailer Plug	7-Way	7-Way	7-Way	7-Way	7-Way
Exterior Lighting	LED	LED	LED	LED	LED
Decking	10-Gauge Steel				
Gate Style	Barn Door Gate				
Ramp Style	Ramps in Carrier				
Ramp Length x Width	66" x 14 3/4"				
Load Capacity (lb.)	6200	6200	6200	6200	6200
Overall Length	17'-4"	19'-4"	21'-4"	19'-4"	21'-4"
Overall Width	102"	102"	102"	102"	102"
Overall Height	58"	58"	58"	58"	58"
Bed Height	28 3/4"	28 3/4"	28 3/4"	28 3/4"	28 3/4"
Bed Length	12'-0"	14'-0"	16'-0"	14'-0"	16'-0"
Bed Width	83"	83"	83"	83"	83"

STANDARD FEATURES

8" Hot Mill Structural Steel Channel Frame 3" Steel Crossmembers 24" Tall Steel Sides Multiple Stake Pockets 6" Hot Mill Structural Steel Channel Tongue 2 5/16" Adjustable Height Coupler Dual Safety Chains and Hooks

7K Drop Leg Jack, Set-Back

10-Gauge, One-piece Steel Deck

(4) D-Ring Tie Downs, Side Mounted Barn Door Gate with Spreader Function (2) 3"x 6' Heavy Ramps in Carrier Formed Tread Plate Fenders Spring Brake Suspension Radial Tires on Steel Wheels Sealed Wiring Harness Full LED, DOT Compliant Lighting Spare Tire Mount

Integrated Tarp Mount and Shroud Tarp Brackets and Tarp Hooks Installed Tarp Scissor Lift - 2-Way 5x16 Cylinder Power Up, Power Down 12V Hydraulic Pump (3000 PSI) Dual Purpose Oversized Pump and Tool Box 12V Deep Cycle Battery and 110V 2-Button Corded Remote