



FEATURES

- 3" x 2" Angle Aluminum Extrusion Frame
- Aluminum Extrusion Tube Uprights & 2"x2" Top Rail
- 3"x 5' ATV Ramp Side Conversions
- Angle Aluminum Extrusion Crosseamers
- 4" Aluminum Triple Tube Tongue
- Radius Fender with Backs
- 15" Aluminum Wheels
- Full DOT Compliant, LED Lighting
- Sealed Wiring Harness
- A-Frame Posi-Lock Coupler
- Dual Safety Chain & Hooks - DOT Approved
- Aluminum Stake Pockets
- 2x8 Treated, #1 Grade Wood - front and rear end caps
- 54" Bi-Fold Gate (2200 lb Rated)

OPTIONS

- 2-5/16" Adjustable Height Coupler
- Aluminum Extruded Deck
- Full Enclosed Wiring
- Utility Stake Pockets
- Spare Tire
- Brake Axle(s)
- Tongue Mounted Toolbox
- **Contact Your Local Dealer for More Options**





ALUMINUM ATV UTILITY

Model Size	82" x 12'	82" x 14'	82" x 14' TA	82" x 16' TA	82" x 18' TA	82" x 20' TA
GAWR (lb/axle)	3500	3500	3500	3500	3500	3500
*Gross Capacity (GWVR)	2990	2990	7000	7000	7000	7000
*Curb Weight (lb)	1000	1090	1585	1650	1740	1900
*Payload Capacity (lb)	1990	1900	5415	5350	5260	5100
Frame Construction	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle
Crossmembers	3"x2" Angle	3"x2" Angle	3" Channel	3" Channel	3" Channel	3" Channel
Top Rail	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube
Uprights/Sides	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube
Tongue Construction	4" Tube	4" Tube	5" Tube	5" Tube	5" Tube	5" Tube
Tongue Length	53"	53"	53"	53"	53"	53"
Coupler	2" A-frame	2" A-frame	2-5/16" A-frame	2-5/16" A-frame	2-5/16" A-frame	2-5/16" A-frame
Coupler Height	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"
Safety Chains & Hooks	Yes	Yes	Yes	Yes	Yes	Yes
Jack	1K Rated Swivel	1K Rated Swivel	2K Rated Set-back	2K Rated Set-back	2K Rated Set-back	2K Rated Set-back
Axle Type	Spring Idler	Spring Idler	Spring Brake	Spring Brake	Spring Brake	Spring Brake
Brakes	-	-	4-wheel Electric	4-wheel Electric	4-wheel Electric	4-wheel Electric
Breakaway Kit w/ Battery	-	-	Yes	Yes	Yes	Yes
Tire Size	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75
Tire Load Range	C	C	C	C	C	C
Tire Ply	Radial	Radial	Radial	Radial	Radial	Radial
Rim Size	15"	15"	15"	15"	15"	15"
Bolt Pattern	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5
Trailer Plug	4-prong	4-prong	7-prong	7-prong	7-prong	7-prong
Exterior Lighting	LED	LED	LED	LED	LED	LED
Decking	No. 1 Grade, Pressure Treated Pine	No. 1 Grade, Pressure Treated Pine	No. 1 Grade, Pressure Treated Pine	No. 1 Grade, Pressure Treated Pine	No. 1 Grade, Pressure Treated Pine	No. 1 Grade, Pressure Treated Pine
Ramp Height	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"	54 1/2"
Ramp Width	79"	79"	79"	79"	79"	79"
Ramp Load Capacity (lb)	2200	2200	2200	2200	2200	2200
Overall Length	16'-9"	18'-9"	18'-9"	20'-9"	22'-9"	24'-9"
Overall Width	100 1/4"	100 1/4"	102"	102"	102"	102"
Overall Height	49"	49"	49"	49"	49"	49"
Deck Height	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"
Deck Length	12'-0"	14'-0"	14'-0"	16'-0"	16'-0"	16'-0"
Deck Width (Between Fenders)	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"

