



# HH SERIES ROUND-TOP CARGO



## FEATURES

- Full Tubular Steel Frame & Tongue
- 24" On-Center Full Tubular Steel Wall Uprights
- 24" On-Center Full Tubular Galvanized Steel Roof Bows
- Formed Channel Steel Crossmembers
- Vapor Barrier
- Fully Undercoated Body
- Weather Coated Tongue & Rear Bulkhead
- Round Roof Design with .030 Aluminum
- Custom Fiberglass Nose Cap
- .030 Aluminum Exterior Sheeting **NEW!**
- 24" Aluminum Tread Plate Rock Guard
- 2K Rated Jack
- Full DOT Compliant, LED Lighting
- Drop Spring Axle (s) & EZ Lube Hubs
- Radial Tires on White Steel Wheels
- Side Door with RV Style, Flush-Lock Latch
- Aluminum Door Hold Back
- Spring Assisted Rear Ramp Door
- 3/4" Engineered Wood Flooring
- 5.2mm Wood Interior Walls
- Aluminum H-Channel Wall Transitions
- Interior 12v LED Dome Light(s) & Switch, Wall Mounted

*Screwless exterior*





# HH SERIES ROUND-TOP CARGO

## Single Axle

Model Size	6' x 10'	6' x 12'	6' x 14'	7' x 10'	7' x 12'
GAWR (lb/axle)	3500	3500	3500	3500	3500
*Gross Capacity (GWWR)	2990	2990	2990	2990	2990
*Curb Weight (lb)	1250	1350	1450	1400	1500
*Payload Capacity (lb)	1740	1640	1540	1590	1490
Frame Construction	3" Tube Steel	3" Tube Steel	3" Tube Steel	4" Tube Steel	4" Tube Steel
Crossmember Spacing	Formed Channel Steel, 24" OC	Formed Channel Steel, 24" OC	Formed Channel Steel, 24" OC	Formed Channel Steel, 24" OC	Formed Channel Steel, 24" OC
Wall Uprights Spacing	Tube Steel 24" OC	Tube Steel 24" OC	Tube Steel 24" OC	Tube Steel 24" OC	Tube Steel 24" OC
Roof Bow Spacing	Galvanized Tube Steel 24" OC	Galvanized Tube Steel 24" OC	Galvanized Tube Steel 24" OC	Galvanized Tube Steel 24" OC	Galvanized Tube Steel 24" OC
Exterior Sheeting	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum
Tongue Construction	3" Tube Steel A-frame	3" Tube Steel A-frame	3" Tube Steel A-frame	4" Tube Steel A-frame	4" Tube Steel A-frame
Tongue Length	39 1/2"	39 1/2"	39 1/2"	42 1/2"	42 1/2"
Coupler	2" A-frame	2" A-frame	2" A-frame	2" A-frame	2" A-frame
Coupler Height	18 3/4"	18 3/4"	18 3/4"	17 1/4"	17 1/4"
Safety Chains & Hooks	Yes	Yes	Yes	Yes	Yes
Jack	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel
Axle Type	Drop Spring Idler	Drop Spring Idler	Drop Spring Idler	Drop Spring Idler	Drop Spring Idler
Brakes	-	-	-	-	-
Breakaway Kit & Battery	-	-	-	-	-
Tire Size	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75
Tire Load Range	C	C	C	C	C
Tire Ply	Radial	Radial	Radial	Radial	Radial
Rim Size	15"	15"	15"	15"	15"
Bolt Pattern	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5
Trailer Plug	4-prong Flat	4-prong Flat	4-prong Flat	4-prong Flat	4-prong Flat
Exterior Lighting	LED	LED	LED	LED	LED
Interior Lighting	12V, LED Dome Light	12V, LED Dome Light	12V, LED Dome Light	12V, LED Dome Light	12V, LED Dome Light
Side Escape Door	Yes	Yes	Yes	Yes	Yes
Side Door Height	62"	62"	62"	62"	62"
Side Door Width	32"	32"	32"	32"	32"
Rear Door Type	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp
Rear Opening Height	68"	68"	68"	68"	68"
Rear Opening Width	66"	66"	66"	78"	78"
Ramp Load Capacity (lb)	1000	1000	1000	1000	1000
Overall Length	14' 3"	16'-1"	17'-10"	14'-0"	16'-1"
Overall Width	93"	93"	93"	102"	102"
Overall Height	95"	95"	95"	95"	95"
Interior Length	10'-8"	12'-9"	14'-9"	10'-9"	12'-9"
Interior Width	69"	69"	69"	81 1/2"	81 1/2"
Between Wheel Wells	-	-	-	-	-
Interior Height	76"	76"	76"	76"	76"
Deck Height	19 1/2"	19 1/2"	19 1/2"	18"	18"
Deck Box Length	9'-10"	11'-10"	13'-10"	9'-10"	11'-10"





# HH SERIES ROUND-TOP CARGO

## Tandem Axle

Model Size	7' x 12' TA	7' x 14' TA	7' x 16' TA	7' x 18' TA	7' x 20' TA
<b>7K Models GAWR (lb/axle)</b>	3500	3500	3500	3500	3500
Gross Capacity (GWVR)	7000	7000	7000	7000	7000
Curb Weight (lb)	1850	2050	2165	2425	2570
Payload Capacity (lb)	5150	4950	4835	4575	4430
<b>10K Models GAWR (lb/axle)</b>	5200	5200	5200	5200	5200
Gross Capacity (GWVR)	9900	9900	9900	9900	9900
Curb Weight (lb)	2100	2280	2400	2695	2770
Payload Capacity (lb)	7800	7620	7500	7205	7130
Frame Construction	4" Tube Steel	4" Tube Steel	4" Tube Steel	6" Tube Steel	6" Tube Steel
Crossmember Spacing	Formed Channel Steel, 16" OC	Formed Channel Steel, 16" OC	Formed Channel Steel, 16" OC	Formed Channel Steel, 16" OC	Formed Channel Steel, 16" OC
Wall Uprights Spacing	Tube Steel 24" OC	Tube Steel 24" OC	Tube Steel 24" OC	Tube Steel 24" OC	Tube Steel 24" OC
Roof Bow Spacing	Galvanized Tube Steel 24" OC	Galvanized Tube Steel 24" OC	Galvanized Tube Steel 24" OC	Galvanized Tube Steel 24" OC	Galvanized Tube Steel 24" OC
Exterior Sheeting	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum
Tongue Construction	4" Tube Steel A-frame	4" Tube Steel A-frame	4" Tube Steel A-frame	6" Tube Steel A-frame	6" Tube Steel A-frame
Tongue Length	38"	38"	38"	38"	38"
Coupler	2-5/16" A-frame	2-5/16" A-frame	2-5/16" A-frame	2-5/16" A-frame	2-5/16" A-frame
Coupler Height	18"	18"	18"	18"	18"
Safety Chains & Hooks	Yes	Yes	Yes	Yes	Yes
Jack	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel
Axle Type	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake
Brakes	Yes	Yes	Yes	Yes	Yes
Breakaway Kit & Battery	Yes	Yes	Yes	Yes	Yes
Tire Size: 7K 10K	ST205/75 ST225/75	ST205/75 ST225/75	ST205/75 ST225/75	ST205/75 ST225/75	ST205/75 ST225/75
Tire Load Range: 7K, 10K	C, D	C, D	C, D	C, D	C, D
Tire Ply	Radial	Radial	Radial	Radial	Radial
Rim Size	15"	15"	15"	15"	15"
Bolt Pattern: 7K 10K	5 on 4.5 6 on 5.5	5 on 4.5 6 on 5.5	5 on 4.5 6 on 5.5	5 on 4.5 6 on 5.5	5 on 4.5 6 on 5.5
Trailer Plug	7-way RV plug	7-way RV plug	7-way RV plug	7-way RV plug	7-way RV plug
Exterior Lighting	LED	LED	LED	LED	LED
Interior Lighting	(2) 12V, LED Dome Light	(2) 12V, LED Dome Light	(2) 12V, LED Dome Light	(2) 12V, LED Dome Light	(2) 12V, LED Dome Light
Side Escape Door	Yes	Yes	Yes	Yes	Yes
Side Door Height	68"	68"	68"	68"	68"
Side Door Width	36"	36"	36"	36"	36"
Rear Door Type	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp
Rear Opening Height	74 1/2"	74 1/2"	74 1/2"	74 1/2"	74 1/2"
Rear Opening Width	78"	78"	78"	78"	78"
Ramp Load Capacity (lb)	1000	1000	1000	1000	1000
Overall Length	16'-2"	18'-2"	20'-2"	22'-2"	24'-2"
Overall Width	102"	102"	102"	102"	102"
Overall Height	8'-6"	8'-6"	8'-6"	8'-6"	8'-6"
Interior Length	12'-9"	14'-9"	16'-9"	18'-9"	20'-9"
Interior Width	81"	81"	81"	81"	81"
Between Wheel Wells	-	-	-	-	-
Interior Height	82"	82"	82"	82"	82"
Deck Height	18"	18"	18"	20"	20"
Deck Box Length	11'-10"	13'-10"	15'-10"	17'-10"	19'-10"





# HH SERIES ROUND-TOP CARGO

## Tandem Axle Cont.

Model Size	8' x 16' TA	8' x 18' TA	8' x 20' TA	101" x 16' TA	101" x 18' TA	101" x 20' TA
<b>7K Models GAWR (lb/axle)</b>	3500	3500	3500	3500	3500	3500
Gross Capacity (GWVR)	7000	7000	7000	7000	7000	7000
Curb Weight (lb)	2350	2670	2800	2600	2750	2830
Payload Capacity (lb)	4650	4330	4200	4400	4250	4170
<b>10K Models GAWR (lb/axle)</b>	5200	5200	5200	5200	5200	5200
Gross Capacity (GWVR)	9900	9900	9900	9900	9900	9900
Curb Weight (lb)	2550	2850	3110	2910	3150	3200
Payload Capacity (lb)	7350	7050	6790	6990	6750	6700
Frame Construction	4" Tube Steel	6" Tube Steel	6" Tube Steel	4" Tube Steel	6" Tube Steel	6" Tube Steel
Crossmember Spacing	Formed Channel Steel, 16" OC	Formed Channel Steel, 16" OC	Formed Channel Steel, 16" OC	Formed Channel Steel, 16" OC	Formed Channel Steel, 16" OC	Formed Channel Steel, 16" OC
Wall Uprights Spacing	Tube Steel 24" OC	Tube Steel 24" OC	Tube Steel 24" OC	Tube Steel 24" OC	Tube Steel 24" OC	Tube Steel 24" OC
Roof Bow Spacing	Galvanized Tube Steel 24" OC	Galvanized Tube Steel 24" OC	Galvanized Tube Steel 24" OC	Galvanized Tube Steel 24" OC	Galvanized Tube Steel 24" OC	Galvanized Tube Steel 24" OC
Exterior Sheeting	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum
Tongue Construction	4" Tube Steel A-frame	6" Tube Steel A-frame	6" Tube Steel A-frame	4" Tube Steel A-frame	6" Tube Steel A-frame	6" Tube Steel A-frame
Tongue Length	41"	41"	41"	41"	41"	41"
Coupler	2-5/16" A-frame	2-5/16" A-frame	2-5/16" A-frame	2-5/16" A-frame	2-5/16" A-frame	2-5/16" A-frame
Coupler Height	18"	18"	18"	18"	18"	18"
Safety Chains & Hooks	Yes	Yes	Yes	Yes	Yes	Yes
Jack	2K Rated Coupler Mount	2K Rated Coupler Mount	2K Rated Coupler Mount	2K Rated Coupler Mount	2K Rated Coupler Mount	2K Rated Coupler Mount
Axle Type	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake
Brakes	Yes	Yes	Yes	Yes	Yes	Yes
Breakaway Kit & Battery	Yes	Yes	Yes	Yes	Yes	Yes
Tire Size: 7K	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75	ST205/75
10K	ST225/75	ST225/75	ST225/75	ST225/75	ST225/75	ST225/75
Tire Load Range:						
7K, 10K	C, D	C, D	C, D	C, D	C, D	C, D
Tire Ply	Radial	Radial	Radial	Radial	Radial	Radial
Rim Size	15"	15"	15"	15"	15"	15"
Bolt Pattern: 7K	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5	5 on 4.5
10K	6 on 5.5	6 on 5.5	6 on 5.5	6 on 5.5	6 on 5.5	6 on 5.5
Trailer Plug	7-way RV Plug	7-way RV Plug	7-way RV Plug	7-way RV Plug	7-way RV Plug	7-way RV Plug
Exterior Lighting	LED	LED	LED	LED	LED	LED
Interior Lighting	(2) 12V, LED Dome Light	(2) 12V, LED Dome Light	(2) 12V, LED Dome Light	(2) 12V, LED Dome Light	(2) 12V, LED Dome Light	(2) 12V, LED Dome Light
Side Escape Door	Yes	Yes	Yes	Yes	Yes	Yes
Side Door Height	68"	68"	68"	68"	68"	68"
Side Door Width	36"	36"	36"	36"	36"	36"
Rear Door Type	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp
Rear Opening Height	74 1/2"	74 1/2"	74 1/2"	74 1/2"	74 1/2"	74 1/2"
Rear Opening Width	90"	90"	90"	90"	90"	90"
Ramp Load Capacity (lb)	4000	4000	4000	4000	4000	4000
Overall Length	20'-6"	22'-6"	24'-6"	20'-6"	22'-6"	24'-6"
Overall Width	102"	102"	102"	102"	102"	102"
Overall Height	104"-105"	104"-105"	104"-105"	104"-105"	104"-105"	104"-105"
Interior Length	16'-9"	18'-9"	20'-9"	16'-9"	18'-9"	20'-9"
Interior Width	93"	93"	93"	93"	93"	93"
Between Wheel Wells	82"	82"	82"	82"	82"	82"
Interior Height	82"	82"	82"	82"	82"	82"
Deck Height	22"-23"	22"-23"	22"-23"	22"-23"	22"-23"	22"-23"
Deck Box Length	15'-10"	17'-10"	19'-10"	15'-10"	17'-10"	19'-10"

