

Wholesale Dealer Pricing

Aluminum Car Hauler

	82" x 16'+2'	82" x 18'+2'	82" x 18'+2' 10K	82" x 20'+2' 10K	82" x 22'+2' 10K
Model	H8218HDAD-070	H8220HDAD-070	H8220HDAD-100	H8222HDAD-100	H8224HDAD-100
GAWR (lb./axle)	3500	3500	5200	5200	5200
GVWR (lb.)	7000	7000	9900	9900	9900
Curb Weight (lb.)	1610	1685	2060	2200	2340
Payload Capacity (lb.)	5390	5315	7840	7700	7560
Frame Construction	6" Aluminum Channel		8" Aluminum Channel		
Crossmembers	3" Aluminum Channel				
Tongue Construction	6" Aluminum Channel, Fully Wrapped				
Coupler	2 5/16" A-frame Posi-Lock				
Coupler Height	14 1/2"				
Safety Chains	Yes				
Jack	2K Rated Set-Back		7K Rated Drop Leg, Set-Back		
Fenders	Removable Aluminum Teardrop				
Axle Type	Leaf Spring Brake				
Hub Type	Easy Lube				
Brakes	4-Wheel Electric				
Breakaway	Battery, Switch, and Lanyard				
Tires	ST205/75R15 'C'		ST225/75R15 'D'		
Wheels	15", 5 on 4.5 Aluminum		15", 6 on 5.5 Aluminum		
Trailer Plug	7-Way				
Exterior Lighting	Full LED, DOT Compliant				
Decking	2" Pressure Treated Pine				
Dovetail	2" Aluminum Extrusion Plank				
Ramp Style	Aluminum Extrusion Slide In				
Ramp Length x Width	60" x 15"				
Ramp Load Capacity (lb.)	4320				
Overall Length	21'-10"	23'-10"	23'-10"	25'-10"	27'-10"
Overall Width	102"	102"	102"	102"	102"
Overall Height	34"	34"	36"	36"	36"
Deck Height	24"	24"	26"	26"	26"
Deck Length	16'-2"	18'-2"	18'-2"	20'-2"	22'-2"
Deck Width	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"

Additional Features

Aluminum Tube Bulkhead
 Ramp Hook Bar and Lockable Ramp Carrier
 Front & Rear End Board Caps
 Aluminum Stake Pockets
 Aluminum Rub Rails
 Sealed Wiring Harness
 Limited 3-Year Warranty