

Wholesale Dealer Pricing

Hydraulic Tail Deckover Trailers

	102"x21'+9'	102"x23'+9'	102"x25'+9'	102"x21'+9'	102"x23'+9'	102"x25'+9'
Model	H21+9HTHD-GN-225	H23+9HTHD-GN-225	H21+9HTHD-GN-259	H21+9HTHD-GN-259	H23+9HTHD-GN-259	H25+9HTHD-GN-259
GAWR (lb./axle)	10000	10000	10000	12000	12000	12000
Gross Capacity (GVWR)	22500	22500	22500	25900	25900	25900
*Curb Weight (lb.)	7350	7800	8200	7840	8100	8800
*Payload Capacity (lb.)	15150	14700	14300	18060	17800	17100
Frame Construction	12" Wide x 14lb/ft Steel I-Beam			12" Wide x 19lb/ft Steel I-Beam		
Crossmembers	3" Steel Channel, 16" OC					
Tongue Construction	12" Wide x 19lb/ft Steel I-Beam					
Tongue Length	8'-6"					
Coupler	2 5/16" Adjustable Height					
Coupler Height	25"-33"					
Safety Chains & Hooks	Yes					
Jack	(2) 12K Rated Drop Leg					
Axle Type	Slipper Spring Brake					
Hub Type	Oil Bath					
Brakes	4-Wheel Electric					
Breakaway Kit	Battery, Switch, and Lanyard					
Tire Size	ST235/80R 16 'E'					
Rim Size	16", 8 on 6.5 Steel Dual					
Breakaway Kit	Battery, Switch, and Lanyard					
Exterior Lighting	Full LED, DOT Compliant					
Decking	2" Pressure Treated Pine					
Dovetail	9' Diamond Plate and Treated Lumber					
Ramp Style	Hydraulic					
Ramp Length x Width	9' x 100"					
Ramp Load Capacity (lb.)	8000					
Ramp Lift/Haul Capacity (lb.)	4000					
Overall Length	38'-6"	40'-6"	42'-6"	38'-6"	40'-6"	42'-6"
Overall Width	102"	102"	102"	102"	102"	102"
Overall Height	71"	71"	71"	71"	71"	71"
Deck Length	20'-2"	25'-2"	30'-2"	20'-2"	25'-2"	30'-2"
Deck Width	97 1/4"	97 1/4"	97 1/4"	97 1/4"	97 1/4"	97 1/4"
Deck Height	33"	33"	33"	33"	33"	33"
Load Angle	18.3 Degree					

Additional Features

Pierced Steel I-Beam Frame

Torque Tube

Gooseneck Hitch

Stake Pockets and Pipe Spools

3/8" Steel Rub Rails

Spare Tire Carrier

Full Width, Lockable Tool/Storage Box

Integrated Winch Mount and Chain Storage

Lockable Underbody Pump Box (Pump and Battery Storage)

Two-Component Epoxy and Polyurethane Primer and Top Coat

18.3 Degree Load Angle

12V, 2 AMP A/C Charger

Solar Battery Maintainer

12V Hydraulic Pump (3000 PSI)

Push Button Control with 15' Lead

Limited 3-Year Warranty

Note: Lift/Haul Capacity is load from center of the ramp forward to the decking .