

Wholesale Dealer Pricing

Low Profile Deckover Trailers

	102"x20'+5' (15K)	102"x25'+5' (15K)	102"x20'+5' (17.6K)	102"x25'+5' (17.6K)
Model: Bumper Pull	H20+5SDBCL-B-150	H25+5SDBCL-B-150	H20+5SDBCL-B-176	H25+5SDBCL-B-176
GAWR (lb./axle)	7000	7000	8000	8000
GVWR (lb.)	15000	15000	17600	17600
Curb Weight	5100	5500	5330	5730
*Payload Capacity (lb.)	9900	9500	12270	11870
Model: Gooseneck	H20+5SDBCL-GN-150	H25+5SDBCL-GN-150	H20+5SDBCL-GN-176	H25+5SDBCL-GN-176
GAWR (lb./axle)	7000	7000	8000	8000
GVWR (lb.)	15000	15000	17600	17600
Curb Weight	5525	6190	5950	6615
*Payload Capacity (lb.)	9475	8810	11650	10985
Frame Construction	12" Wide x 14lb/ft Steel I-Beam			
Crossmembers	3" Steel Channel, 16" OC			
Tongue Construction	12" Wide x 14lb/ft Steel I-Beam			
Tongue Length	8'-6"			
Coupler: Bumper Pull	Pintle			
Gooseneck	2-5/16" Adjustable Height			
Coupler Height	29"-37"			
Safety Chains & Hooks	Yes			
Jack	(2) 12K Rated Drop Leg			
Axle Type	Slipper Spring Brake			
Hub Type	Easy Lube		Oil Bath	
Brakes	4-Wheel Electric			
Breakaway Kit	Battery, Switch, and Lanyard			
Tires	ST235/80R16 'E'		ST215/75R17.5 'J'	
Wheels	16", 8 on 6.5 Steel		17.5", 8 on 6.5 Steel	
Trailer Plug	7-Way			
Exterior Lighting	Full LED, DOT Compliant			
Decking	2" Pressure Treated Pine			
Dovetail	5' Self Cleaning			
Ramp Style	Double Spring Assist, Fold-Over Full Width			
Ramp Length x Width	57" x 45"			
Ramp Load Capacity (lb.)	11500			
Overall Length: Bumper Pull	28'-6"	33'-6"	28'-6"	33'-6"
Gooseneck	33'-6"	38'-6"	33'-6"	38'-6"
Overall Width	102"	102"	102"	102"
Overall Height	75"	75"	75"	75"
Deck Length	20'-2"	25'-2"	20'-2"	25'-2"
Deck Width	97 1/4"	97 1/4"	97 1/4"	97 1/4"
Deck Height	33"	33"	33"	33"

Additional Features

Low Profile Pierced Beam Frame
 Steel Steel Channel Sides
 Front & Rear End Board Caps
 Stake Pockets and Pipe Spools
 1/4" Steel Rub Rails (15K Models)
 3/8" Steel Rub Rails (17.6K Models)

Spare Tire Mount, Recessed In Neck
 Lockable Solid Steel Storage Tray
 Mud Flaps
 High Gloss Powder Coat Finish
 Sealed Wiring Harness
 Limited 3-Year Warranty