

## **Specification Page**

## DECKOVER DUMP

**DUMP TRAILERS** 





	96" x 14' (14K)	96" x 16' (14K)
Model	STH9614HLODOD-B-140	STH9616HLODOD-B-140
GAWR (lb./axle)	7000	7000
GVWR (lb.)	14000	14000
Curb Weight (lb.)	4140	4400
Payload Capacity (lb.)	9860	9600
Frame Construction	6" Channel	6" Channel
Crossmembers	4" Channel	4" Channel
Sides	20" Tall, Fold Down Steel	20" Tall, Fold Down Steel
Tongue Construction	8" Channel	8" Channel
Coupler	2 5/16" Adj. Height	2 5/16" Adj. Height
Coupler Height	12.5"-20.5"	12.5"-20.5"
Safety Chains	Yes	Yes
Jack	12K Rated Drop Leg	12K Rated Drop Leg
Axle Type	Leaf Spring Brake	Leaf Spring Brake
Brakes	Yes	Yes
Breakaway Kit	Yes	Yes
Tires	ST235/80R16 'E'	ST235/80R16 'E'
Wheels	16", 8 on 6.5	16", 8 on 6.5
Trailer Plug	7-Way	7-Way
Exterior Lighting	LED	LED
Decking	7-Gauge Steel	7-Gauge Steel
Gate Style	Combo Barn Gate	Combo Barn Gate
Ramp Style	Ramps in Carrier	Ramps in Carrier
Ramp Length x Width	90" x 14 3/4"	90" x 14 3/4"
Load Capacity (lb.)	7100	7100
Overall Length	18'-6"	20'-6"
Overall Width	102"	102"
Overall Height	54"	58"
Bed Height	34"	34"
Bed Length	14'-0"	16-0"
Bed Width	96"	96"

## STANDARD FEATURES

6" Steel Channel Frame 4" Steel Channel Crossmembers 20" Tall. Fold-Down Sides 8" Steel Channel Tongue 2 5/16" Adjustable Height Gooseneck Coupler **Dual Safety Chains and Hooks** 

Dual, 12K Drop Leg Jacks 7-Gauge, 96" Wide Deck (5) D-Ring Tie Downs, Side Mounted

Barn Door Gate with Spreader Function (2) 3"x 90" Heavy Ramps in Carrier Formed Tread Plate Fenders Spring Brake Suspension with Easy Lube Hubs Radial Tires on Black Steel Wheels Sealed Wiring Harness Full LED, DOT Compliant Lighting Underbody Spare Tire Tub Stabilizer Jack Receivers (Jacks Sold Separately) Integrated Tarp Mount and Shroud Tarp Brackets and Tarp Hooks Installed Tarp Underbody Secure Tool Storage Scissor Lift Power Up, Gravity Down 12V Hydraulic Pump (3000 PSI) Dual Purpose Oversized Pump and Tool Box 12V Deep Cycle Battery and 110V Battery Charger 2-Button Corded Remote