

Wholesale Dealer Pricing

Gravity Tilt Tandem Axle Equipment Trailer

	Full Tilt Models					Stationary Deck Models			
	82" x 16'	82" x 18'	82" x 20'	82" x 16'+4'	82" x 16'+6'	82" x 18'+4'	82" x 18'+6'	82" x 20'+4'	82" x 20'+6'
Model: 14K	H16GTL-140	H18GTL-140	H20GTL-140	H16+4GTL-140	H16+6GTL-140	H18+4GTL-140	H18+6GTL-140	H20+4GTL-140	H20+6GTL-140
16K	H16GTL-160	H18GTL-160	H20GTL-160	H16+4GTL-160	H16+6GTL-160	H18+4GTL-160	H18+6GTL-160	H20+4GTL-160	H20+6GTL-160
GAWR (lb./axle): 14K	7000	7000	7000	7000	7000	7000	7000	7000	7000
16K	8000	8000	8000	8000	8000	8000	8000	8000	8000
GVWR (lb.): 14K	14000	14000	14000	14000	14000	14000	14000	14000	14000
16K	16000	16000	16000	16000	16000	16000	16000	16000	16000
Curb Weight (lb.): 14K	3460	3400	3740	3200	3310	3310	3540	3540	3700
16K	3960	3900	4240	3710	3910	3910	4100	4100	4900
Payload Capacity (lb.): 14K	10540	10600	10260	10800	10690	10690	10460	10460	10300
16K	12040	12100	11760	12290	12090	12090	11900	11900	11100
Frame Construction: 14K	6" Steel Channel				6" Steel Channel				
16K	8" Steel Channel				8" Steel Channel				
Crossmembers	3" Steel Channel, 16" OC				3" Steel Channel, 16" OC				
Tongue Construction	6" Steel Channel, Wrapped				6" Steel Channel, Wrapped				
Coupler	2 5/16" Adjustable Height				2 5/16" Adjustable Height				
Coupler Height	11"-19"				11"-19"				
Safety Chains & Hooks	Yes				Yes				
Jack	12K Drop Leg				12K Drop Leg				
Fenders	Double Break Tread Plate				Double Break Tread Plate				
Axle Type	Drop Spring Brake				Drop Spring Brake				
Brakes	4-Wheel Electric				4-Wheel Electric				
Breakaway Kit	Battery, Switch, and Lanyard				Battery, Switch, and Lanyard				
Tire Size: 14K	ST235/80R16 'E'				ST235/80R16 'E'				
16K	ST215/75R17.5 'J'				ST215/75R17.5 'J'				
Wheels: 10K	16", 8 on 6.5				16", 8 on 6.5				
16K	17.5", 8 on 6.5				17.5", 8 on 6.5				
Trailer Plug	7-Way				7-Way				
Exterior Lighting	LED				LED				
Decking	2" Pressure Treated Pine				2" Pressure Treated Pine				
Dovetail	Reverse Taper Cut				Reverse Taper Cut				
Ramp Style	None				None				
Overall Length	24'-5"	26'-5"	28'-5"	24'-5"	26'-5"	26'-5"	28'-5"	28'-5"	30'-5"
Overall Width	102"	102"	102"	102"	102"	102"	102"	102"	102"
Overall Height: 14K	32"	32"	32"	32"	32"	32"	32"	32"	32"
16K	34"	34"	34"	34"	34"	34"	34"	34"	34"
Deck Height: 14K	19 1/2"	19 1/2"	19 1/2"	19 1/2"	19 1/2"	19 1/2"	19 1/2"	19 1/2"	19 1/2"
16K	21"	21"	21"	21"	21"	21"	21"	21"	21"
Deck Length (Includes Stationary)	16'-2"	18'-2"	20'-2"	20'-4"	22'-4"	22'-4"	24'-4"	24'-4"	26'-4"
Stationary Deck Width	80"	80"	80"	80"	80"	80"	80"	80"	80"
Tilting Deck Width	73-3/4"	73-3/4"	73-3/4"	73-3/4"	73-3/4"	73-3/4"	73-3/4"	73-3/4"	73-3/4"
Between Fenders Width	81-3/4"	81-3/4"	81-3/4"	81-3/4"	81-3/4"	81-3/4"	81-3/4"	81-3/4"	81-3/4"
Load Angle	11 Deg.	10 Deg.	9 Deg.	11 Deg.	11 Deg.	10 Deg.	10 Deg.	9 Deg.	9 Deg.

Additional Features

HD Tube Bulkhead	High Gloss Powder Coat Finish
Front & Rear End Board Caps	Sealed Wiring Harness
Stake Pockets	Hydraulic Cushion Load Cylinder
Heavy Duty Hinge Latches	Cylinder Shut-Off Valve
Spare Tire Mount	Limited 3-Year Warranty