

Wholesale Dealer Pricing

Industrial Equipment Trailer

	82" x 14'+2'	82" x 16'+2'	82" x 18'+2'	82" x 20'+2'	82" x 22'+2'
Model	H8216IL-140	H8218IL-140	H8220IL-140	H8222IL-140	H8224IL-140
GAWR (lb./axle)	7000	7000	7000	7000	7000
GVWR (lb.)	14000	14000	14000	14000	14000
Curb Weight (lb.)	2690	2860	3030	3300	3570
Payload Capacity (lb.)	11310	11140	10970	10700	10430
Frame Construction	6" Steel Channel				
Crossmembers	3" Steel Channel, 16" OC				
Tongue Construction	6" Steel Channel, Fully Wrapped				
Tongue Length	60"				
Coupler	2-5/16" Adjustable Height				
Coupler Height	11"-22"				
Safety Chains	Yes				
Jack	12K Rated Drop Leg				
Fenders	Steel Formed Tread Plate				
Axle Type	Slipper Spring Brake				
Hub Type	Easy Lube				
Brakes	4-Wheel Electric				
Breakaway Kit	Battery, Switch, and Lanyard				
Tires	ST235/80R16 'E'				
Wheels	16", 8 on 6.5				
Trailer Plug	7-Way				
Exterior Lighting	Full LED, DOT Compliant				
Decking	2" Pressure Treated Pine				
Dovetail	2' Steel Tread Plate				
Ramp Style	Hinged, Spring Assisted				
Ramp Length x Width	60" x 21"				
Ramp Load Capacity (lb.)	6500				
Overall Length	22'-14"	24'-14"	25'-14"	28'-14"	30'-14"
Overall Width	102"	102"	102"	102"	102"
Overall Height	76.5"	76.5"	76.5"	76.5"	76.5"
Deck Length	14'-2"	16'-2"	18'-2"	20'-2"	22'-2"
Deck Width	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"
Deck Height	25 1/2"	25 1/2"	25 1/2"	25 1/2"	25 1/2"

Additional Features

Custom Formed Tube Bulkhead
 Front & Rear End Board Caps
 Stake Pockets
 Spare Tire Mount
 High Gloss Powder Coat Finish
 Sealed Wiring Harness
 Limited 3-Year Warranty