

H&H Open Trailer Models

Rail Side Single Axle Aluminum Utility Trailers

	60" x 8'	66" x 10'	76" x 10'	76" x 12'	82" x 12'	82" x 14'
Model	H6008RSA-030	H6610RSA-030	H7610RSA-030	H7612RSA-030	H8212RSA-030	H8214RSA-030
GAWR (lb./axle)	3500	3500	3500	3500	3500	3500
*Gross Capacity (GWVR)	2990	2990	2990	2990	2990	2990
*Curb Weight (lb.)	650	810	830	920	980	1050
*Payload Capacity (lb.)	2340	2180	2160	2070	2010	1940
Frame Construction	3" x 2" Aluminum Angle					
Crossmembers	3" x 2" Aluminum Angle					
Tongue Construction	4" Triple Aluminum Tube					
Tongue Length	42 1/2"					
Top Rail	2" x 2" Aluminum Tube					
Uprights	2" x 1-1/2" Aluminum Tube					
Coupler	2" A-frame					
Coupler Height	14 1/2"					
Safety Chains & Hooks	Yes					
Jack	1K Rated Swivel with Caster					
Fenders	Smooth Aluminum					
Axle Type	Leaf Spring Idler					
Hub Type	Easy Lube					
Brakes	-					
Breakaway	-					
Tire Size	ST205/75R15C 6-PR					
Rim Size	15", 5 on 4.5 Aluminum					
Trailer Plug	4-prong					
Exterior Lighting	Full LED, DOT Compliant					
Decking	2" Pressure Treated Pine					
Ramp Style	Aluminum Extrusion Bi-fold					
Ramp Length x Width	54 1/2" x 57"	54 1/2" x 63"	54 1/2" x 73"	54 1/2" x 73"	54 1/2" x 79"	54 1/2" x 79"
Ramp Load Capacity (lb.)	2200	2200	2200	2200	2200	2200
Overall Length	11'-10"	13'-9"	14'-4"	16'-4"	16'-9"	18'-9"
Overall Width	78 1/4"	84 1/4"	94 1/4"	94 1/4"	100 1/4"	100 1/4"
Overall Height	49"	49"	49"	49"	49"	49"
Deck Height	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"
Deck Length	8'-0"	10'-0"	10'-0"	12'-0"	12'-0"	14'-0"
Deck Width	60 1/4"	66 1/4"	76 1/4"	76 1/4"	82 1/4"	82 1/4"

Additional Features

Front & Rear End Board Caps

Aluminum Stake Pockets

Sealed Wiring Harness

Limited 3-Year Warranty

H&H Open Trailer Models

Rail Side Tandem Axle Aluminum Utility Trailers

	82" x 14' TA	82" x 16' TA	82" x 18' TA	82" x 20' TA
Model	H8214TRSA-070	H8216TRSA-070	H8218TRSA-070	H8220TRSA-070
GAWR (lb./axle)	3500	3500	3500	3500
*Gross Capacity (GWVR)	7000	7000	7000	7000
*Curb Weight (lb.)	1485	1550	1640	1800
*Payload Capacity (lb.)	5515	5450	5360	5200
Frame Construction	3" x 2" Aluminum Angle Extrusion			
Crossmembers	3" Aluminum Channel			
Tongue Construction	5" Aluminum Triple Tube			
Tongue Length	53"			
Top Rail	2" x 2" Aluminum Tube			
Uprights	2" x 1-1/2" Aluminum Extrusion Tube			
Coupler	2 5/16" A-frame			
Coupler Height	14 1/2"			
Safety Chains & Hooks	Yes			
Jack	2K Rated Set-Back			
Fenders	Smooth Aluminum Teardrop			
Axle Type	Leaf Spring Brake			
Hub Type	Easy Lube			
Brakes	4-Wheel Electric			
Breakaway	Battery, Switch, and Lanyard			
Tire Size	ST205/75R15C 6-PR			
Rim Size	15", 5 on 4.5 Aluminum			
Trailer Plug	7-Way			
Exterior Lighting	Full LED, DOT Compliant			
Decking	2" Pressure Treated Pine			
Ramp Style	Aluminum Extrusion Bi-fold			
Ramp Length x Width	54 1/2" x 79"			
Ramp Load Capacity (lb.)	2200			
Overall Length	18'-9"	20'-9"	22'-9"	24'-9"
Overall Width	102"	102"	102"	102"
Overall Height	49"	49"	49"	49"
Deck Height	18 1/2"	18 1/2"	18 1/2"	18 1/2"
Deck Length	14'-0"	16'-0"	18'-0"	20'-0"
Deck Width	82 1/4"	82 1/4"	82 1/4"	82 1/4"

Additional Features:

(2) 3" x 5' Side Aluminum Ramp Conversions

Front & Rear End Board Caps

Aluminum Stake Pockets

Sealed Wiring Harness

Limited 3-Year Warranty