

Wholesale Dealer Pricing

Solid Side Aluminum Utility

	60" x 8'	66" x 10'	76" x 10'	76" x 12'	82" x 12'	82" x 14'
Model	H6008SSA-030	H6610SSA-030	H7610SSA-030	H7612SSA-030	H8212SSA-030	H8214SSA-030
GAWR (lb./axle)	3500	3500	3500	3500	3500	3500
*Gross Capacity (GWVR)	2990	2990	2990	2990	2990	2990
*Curb Weight (lb.)	740	850	880	1010	1040	1130
*Payload Capacity (lb.)	2250	2140	2110	1980	1950	1860
Frame Construction	Formed 1/8" Polished Aluminum Diamond Plate					
Crossmembers	3" Aluminum Channel					
Tongue Construction	4" Aluminum Triple Tube					
Tongue Length	42"					
Top Rail	None					
Uprights/Sides	Formed 1/8" Polished Aluminum Diamond Plate Sides, 15" Tall					
Coupler	2" A-frame					
Coupler Height	14 1/2"					
Safety Chains & Hooks	Yes					
Jack	1K Rated Swivel with Caster					
Fenders	Smooth Aluminum					
Axle Type	Leaf Spring Idler					
Hub Type	Easy Lube					
Brakes	-					
Breakaway	-					
Tire Size	ST205/75R15C 6-PR					
Rim Size	15", 5 on 4.5 Aluminum					
Trailer Plug	4-prong					
Exterior Lighting	Full LED, DOT Compliant					
Decking	2" Pressure Treated Pine					
Ramp Style	Aluminum Extrusion Bi-fold					
Ramp Length x Width	54 1/2" x 57"	54 1/2" x 63"	54 1/2" x 73"	54 1/2" x 73"	54 1/2" x 79"	54 1/2" x 79"
Ramp Load Capacity (lb.)	2200	2200	2200	2200	2200	2200
Overall Length	11'-10"	13'-10"	14'-4"	16'-4"	16'-9"	18'-9"
Overall Width	78 1/4"	85 1/4"	94 1/4"	94 1/4"	100 1/4"	100 1/4"
Overall Height	49"	49"	49"	49"	49"	49"
Deck Length	8'-0"	10'-0"	10'-0"	12'-0"	12'-0"	14'-0"
Deck Width	60 1/4"	66 1/4"	76 1/4"	76 1/4"	82 1/4"	82 1/4"
Deck Height	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"

Additional Features

Front & Rear End Board Caps

D-Rings

Sealed Wiring Harness

Limited 3-Year Warranty