

H&H Open Trailer Models

Rail Side Single Axle Steel Utility Trailer

	60" x 8'	66" x 10'	76" x 10'	76" x 12'	82" x 12'	82" x 14'
Model	H6008RS-030	H6610RS-030	H7610RS-030	H7612RS-030	H8212RS-030	H8214RS-030
GAWR (lb./axle)	3500	3500	3500	3500	3500	3500
*Gross Capacity (GVWR)	2990	2990	2990	2990	2990	2990
*Curb Weight (lb.)	750	890	970	1050	1110	1210
*Payload Capacity (lb.)	2240	2100	2020	1940	1880	1780
Frame Construction	3" x 2"x 3/16" Steel Angle					
Crossmembers	3" x 2"x 3/16" Steel Angle					
Tongue Construction	4" Steel Channel					
Tongue Length	45"					
Top Rail	2" x 2" Steel Tube					
Uprights/Sides	2" x 1-1/2" Steel Tube					
Coupler	2" A-frame					
Coupler Height	17 1/2"					
Safety Chains & Hooks	Yes					
Jack	2K Rated Set-Back					
Fenders	Steel Tread Plate					
Axle Type	Leaf Spring Idler					
Hub Type	Easy Lube					
Brakes	-					
Breakaway	-					
Tire Size	ST205/75R15C 6-PR					
Rim Size	15", 5 on 4.5 Steel					
Trailer Plug	4-prong					
Exterior Lighting	Full LED, DOT Compliant					
Decking	2" Pressure Treated Pine					
Ramp Style	Mesh Steel, Spring Assist Gate					
Ramp Length x Width	50" x 55"	50" x 61"	50" x 71"	50" x 71"	50" x 77"	50" x 77"
Ramp Load Capacity (lb.)	2500	2500	2500	2500	2500	2500
Overall Length	12'-2"	14'-2"	14'-2"	16'-2"	16'-2"	18'-2"
Overall Width	80 1/2"	86 1/2"	94 1/2"	94 1/2"	102"	102"
Overall Height	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"	70 1/4"
Deck Length	8'-2"	10'-2"	10'-2"	12'-2"	12'-2"	14'-2"
Deck Width	60 1/4"	66 1/4"	76 1/4"	76 1/4"	82 1/4"	82 1/4"
Deck Height	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"	20 1/4"

Additional Features:

- Welded Front Board Retainer
- Rear End Board Cap
- Stake Pockets
- Spare Tire Mount
- High Gloss Powder Coat Finish
- Enclosed Sealed Wiring Harness
- Limited 3-Year Warranty

H&H Open Trailer Models

Rail Side Tandem Axle Steel Utility Trailer

	82" x 14' TA	82" x 16' TA	82" x 18' TA	82" x 20' TA
Model	H8214TRS-070	H8216TRS-070	H8218TRS-070	H8220TRS-070
GAWR (lb./axle)	3500	3500	3500	3500
*Gross Capacity (GVWR)	7000	7000	7000	7000
*Curb Weight (lb.)	1610	1790	1890	1970
*Payload Capacity (lb.)	5390	5210	5110	5030
Frame Construction	4" x 3" x 1/4" Steel Angle			
Crossmembers	3" x 2" x 3/16" Steel Angle			
Tongue Construction	4" Steel Channel, Fully Wrapped			
Tongue Length	45"			
Top Rail	2" x 2" Steel Tube			
Uprights/Sides	2" x 1-1/2" Steel Tube			
Coupler	2 5/16" A-frame			
Coupler Height	17 1/2"			
Safety Chains & Hooks	Yes			
Jack	2K Rated Set-Back			
Fender	Steel Formed Tread Plate			
Axle Type	Leaf Spring Brake			
Hub Type	Easy Lube			
Brakes	4-Wheel Electric			
Breakaway	Battery, Switch, and Lanyard			
Tire Size	ST205/75R15C 6-PR			
Rim Size	15", 5 on 4.5 Steel			
Trailer Plug	7-Way			
Exterior Lighting	Full LED, DOT Compliant			
Decking	2" Pressure Treated Pine			
Ramp Style	Mesh Steel, Spring Assist Gate			
Ramp Length x Width	50" x 77"			
Ramp Load Capacity (lb.)	2500			
Overall Length	18'-2"	20'-2"	22'-2"	24'-2"
Overall Width	102"	102"	102"	102"
Overall Height	70 1/4"	70 1/4"	70 1/4"	70 1/4"
Deck Length	14'-2"	16'-2"	18'-2"	20'-2"
Deck Width	82 1/4"	82 1/4"	82 1/4"	82 1/4"
Deck Height	20 1/4"	20 1/4"	20 1/4"	20 1/4"

Additional Features

Welded Front Board Retainer
 Rear End Board Cap
 Stake Pockets
 Spare Tire Mount
 High Gloss Powder Coat Finish
 Enclosed Sealed Wiring Harness
 Limited 3-Year Warranty