

Wholesale Dealer Pricing

Single Axle Gravity Tilt Equipment Trailer

	62" x 10' (6K)	78" x 12' (7K)	78" x 12'+4' (7K)	78" x 12' (10K)	78" x 12'+4' (10K)
Model	H6210GTL-060	H7812GTL-078	H7812+4GTL-078	H7812GTL-100	H7812+4GTL-100
GAWR (lb./axle)	5200	7000	7000	8000	8000
GVWR (lb.)	6000	7800	7800	9900	9900
Curb Weight (lb.)	1390	1900	2150	2250	2500
Payload Capacity (lb.)	4610	5900	5650	7650	7400
Frame Construction	5"x2" Steel Tube				
Crossmembers	3" Steel Channel, 16" OC				
Tongue Construction	5" Steel Channel				
Coupler	2 5/16" Adjustable Height				
Coupler Height	8"-17"				
Safety Chains	Yes				
Jack	7K Drop Leg Set-Back				
Fenders	Steel Formed Tread Plate				
Axle Type	Torsion Brake				
Hub Type	Easy Lube			Oil Bath	
Brakes	4-Wheel Electric				
Breakaway Kit	Battery, Switch, and Lanyard				
Tires	ST225/75R15 'D'	ST235/80R16 'E'		ST215/75R17.5 'J'	
Wheels	15", 6 on 5.5	16", 8 on 6.5		17.5", 8 on 6.5	
Trailer Plug	7-Way				
Exterior Lighting	Full LED, DOT Compliant				
Decking	Pressure Treated Pine				
Dovetail	Diamond Plate Knife Edge Tail				
Ramp Style	None				
Ramp Length x Width	-	-	-	-	-
Ramp Load Capacity (lb.)	-	-	-	-	-
Overall Length	15'-10"	17'-10"	22'	17'-10"	22'
Overall Width	86"	102"	102"	102"	102"
Overall Height	32"	32"	32"	34"	34"
Tilt Deck Length	10'-10"	12'-10"	17'	12'-10"	17'
Stationary Deck Length	-	-	4'	-	4'
Deck Width (Between Fenders)	62"	78"	78"	78"	78"
Deck Height	17"	19"	19"	21"	21"
Load Angle	12 Deg.	11 Deg.	11 Deg.	11 Deg.	11 Deg.

Additional Features

HD Tube Bulkhead
 Front & Rear End Board Caps
 Stake Pockets
 D-Rings
 Lockable Tongue Mounted Toolbox
 High Gloss Powder Coat Finish
 Hydraulic Cushion Load Cylinder
 Sealed Wiring Harness