



\*Shown with optional drive-over fenders

## FEATURES

- Steel Channel Frame & Crossmembers
- Fully Wrapped, Channel Steel Tongue
- Adjustable Height Coupler & Dual Safety Chains
- 12K Drop Leg Jack
- Treated, #1 Grade Wood Deck - front and rear end caps
- Leaf Spring Brake Suspension & EZ Lube Hubs
- Radial Tires on Steel Wheels
- Spare Tire Mount
- Full DOT Compliant, LED Lighting
- Sealed Wiring Harness
- 2' Steel Tread Plate Dovetail – 10° of slope
- 3"×5' Hinged, Spring Assisted Skid Loader Ramps (6500 lb Load Rating)
- Stake Pockets
- Bulkhead

## OPTIONS

- Steel Drive-Over Fenders
- Outrigger Deck Extensions
- D-Rings & Rub Rail
- Spare Tire
- Multiple Color Options Available
- **Contact Your Local Dealer for More Options**



\*Shown with optional spare tire



# INDUSTRIAL FLATBED

Model Size	82" x 14'+2'	82" x 16'+2'	82" x 18'+2'	82" x 20'+2'	82" x 22'+2'	82" x 24'+2'	82" x 26'+2'
GAWR (lb/axle)	7000	7000	7000	7000	7000	7000	7000
*Gross Capacity (GVWR)	14000	14000	14000	14000	14000	14000	14000
*Curb Weight (lb)	2690	2860	3030	3300	3570	4010	4310
*Payload Capacity (lb)	11310	11140	10970	10700	10430	9990	9690
Frame Construction	6" Channel	6" Channel	6" Channel	6" Channel	6" Channel	8" Channel	8" Channel
Crossmembers	3" Channel 16" OC	3" Channel 16" OC	3" Channel 16" OC	3" Channel 16" OC	3" Channel 16" OC	3" Channel 16" OC	3" Channel 16" OC
Tongue Construction	6" Channel, Fully Wrapped	6" Channel, Fully Wrapped	6" Channel, Fully Wrapped	6" Channel, Fully Wrapped	6" Channel, Fully Wrapped	6" Channel, Fully Wrapped	6" Channel, Fully Wrapped
Tongue Length	60"	60"	60"	60"	60"	60"	60"
Coupler	2-5/16" A-frame	2-5/16" A-frame	2-5/16" A-frame	2-5/16" A-frame	2-5/16" A-frame	2-5/16" A-frame	2-5/16" A-frame
Coupler Height	16 3/4"	16 3/4"	16 3/4"	16 3/4"	16 3/4"	16 3/4"	16 3/4"
Safety Chains & Hooks	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Jack	12K Drop Leg	12K Drop Leg	12K Drop Leg	12K Drop Leg	12K Drop Leg	12K Drop Leg	12K Drop Leg
Axle Type	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake
Brakes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Breakaway Kit & Battery	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Tire Size	ST235/80	ST235/80	ST235/80	ST235/80	ST235/80	ST235/80	ST235/80
Tire Load Range	E	E	E	E	E	E	E
Tire Ply	Radial	Radial	Radial	Radial	Radial	Radial	Radial
Rim Size	16"	16"	16"	16"	16"	16"	16"
Bolt Pattern	8 on 6.5	8 on 6.5	8 on 6.5	8 on 6.5	8 on 6.5	8 on 6.5	8 on 6.5
Trailer Plug	7-prong	7-prong	7-prong	7-prong	7-prong	7-prong	7-prong
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED
Decking	No. 1 Grade, Pressure Treated Pine	No. 1 Grade, Pressure Treated Pine	No. 1 Grade, Pressure Treated Pine	No. 1 Grade, Pressure Treated Pine	No. 1 Grade, Pressure Treated Pine	No. 1 Grade, Pressure Treated Pine	No. 1 Grade, Pressure Treated Pine
Dovetail	2' Steel Treadplate	2' Steel Treadplate	2' Steel Treadplate	2' Steel Treadplate	2' Steel Treadplate	2' Steel Treadplate	2' Steel Treadplate
Ramp Style	Hinged, Spring Assisted	Hinged, Spring Assisted	Hinged, Spring Assisted	Hinged, Spring Assisted	Hinged, Spring Assisted	Hinged, Spring Assisted	Hinged, Spring Assisted
Ramp Height	60"	60"	60"	60"	60"	60"	60"
Ramp Width	21"	21"	21"	21"	21"	21"	21"
Ramp Load Capacity (lb)	6500	6500	6500	6500	6500	6500	6500
Overall Length	19'-10"	21'-10"	23'-10"	25'-10"	27'-10"	29'-10"	30'-10"
Overall Width	102"	102"	102"	102"	102"	102"	102"
Overall Height	33"	33"	33"	33"	33"	34"	34"
Deck Height	24 1/4"	24 1/4"	24 1/4"	24 1/4"	24 1/4"	24 1/4"	24 1/4"
Deck Length	14'-2"	16'-2"	18'-2"	20'-2"	22'-2"	24'-2"	26'-2"
Deck Width (Between Fenders)	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"

