

## Wholesale Dealer Pricing

### Topline I-Beam Tilt Bed Equipment Trailer

|                                    | 82" x 16'+4"                             | 82" x 16'+6"     | 82" x 18'+4"     | 82" x 18'+6"                     |
|------------------------------------|--|------------------|------------------|----------------------------------|
| <b>Model</b>                       | HBTE82164-BP-154                         | HBTE82166-BP-154 | HBTE82184-BP-154 | HBTE82186-BP-154                 |
| <b>GAWR (lb./axle)</b>             | 7000                                     | 7000             | 7000             | 7000                             |
| <b>GVWR (lb.)</b>                  | 15400                                    | 15400            | 15400            | 15400                            |
| <b>Curb Weight (lb.)</b>           | 4040                                     | 4180             | 4180             | 4380                             |
| <b>Payload Capacity (lb.)</b>      | 11360                                    | 11220            | 11220            | 11020                            |
| <b>Model</b>                       | HBTE82164-BP-176                         | HBTE82166-BP-176 | HBTE82184-BP-176 | HBTE82186-BP-176                 |
| <b>GAWR (lb./axle)</b>             | 8000                                     | 8000             | 8000             | 8000                             |
| <b>GVWR (lb.)</b>                  | 17600                                    | 17600            | 17600            | 17600                            |
| <b>Curb Weight (lb.)</b>           | 4220                                     | 4420             | 4420             | 4620                             |
| <b>Payload Capacity (lb.)</b>      | 13380                                    | 13180            | 13180            | 12980                            |
| <b>Model</b>                       | HBTE82164-BP-220                         | HBTE82166-BP-220 | HBTE82184-BP-220 | N/A                              |
| <b>GAWR (lb./axle)</b>             | 10000                                    | 10000            | 10000            | N/A                              |
| <b>GVWR (lb.)</b>                  | 22000                                    | 22000            | 22000            | N/A                              |
| <b>Curb Weight (lb.)</b>           | 4620                                     | 4820             | 4820             | N/A                              |
| <b>Payload Capacity (lb.)</b>      | 17380                                    | 17180            | 17180            | N/A                              |
| <b>Frame Construction</b>          | 8", 13# I-Beam                           |                  |                  | 8", 15# I-Beam                   |
| <b>Tilt Deck Frame</b>             | 6" x 4" x 5/16" Reinforced Angle         |                  |                  | 6" x 6" x 5/16" Reinforced Angle |
| <b>Tilt Deck Crossmembers</b>      | 3" x 2" 11ga Tube (16" On-Center)        |                  |                  |                                  |
| <b>Tongue Construction</b>         | 8", 13# I-Beam                           |                  |                  |                                  |
| <b>Coupler</b>                     | 4-Bolt Nose Plate Adjustable Pintle Ring |                  |                  |                                  |
| <b>Coupler Height</b>              | 17"-26"                                  | 17"-26"          | 17"-26"          | 17"-26"                          |
| <b>Safety Chains &amp; Hooks</b>   | Yes                                      |                  |                  |                                  |
| <b>Jack</b>                        | HD 2-Speed, 12K Rated Drop Leg           |                  |                  |                                  |
| <b>Fenders</b>                     | HD Reinforced Tread Plate                |                  |                  |                                  |
| <b>Suspension</b>                  | Slipper Spring Brake, Easy Lube Hubs     |                  |                  |                                  |
| <b>17.6K / 22K</b>                 | Slipper Spring Brake, Oil Bath Hubs      |                  |                  |                                  |
| <b>Brakes</b>                      | 4-Wheel Electric                         |                  |                  |                                  |
| <b>Breakaway Kit</b>               | Battery, Switch, and Lanyard             |                  |                  |                                  |
| <b>Tires</b>                       | ST235/80R16 'E'                          |                  |                  |                                  |
| <b>17.6K / 22K</b>                 | ST215/75R17.5 'J'                        |                  |                  |                                  |
| <b>Wheels</b>                      | 16" Black Steel Wheels, 8 on 6.5         |                  |                  |                                  |
| <b>17.6K / 22K</b>                 | 17.5" Silver Steel Wheels, 8 on 6.5      |                  |                  |                                  |
| <b>Trailer Plug</b>                | 7-Way RV-Style                           |                  |                  |                                  |
| <b>Exterior Lighting</b>           | Full LED, DOT Compliant                  |                  |                  |                                  |
| <b>Finish</b>                      | High Gloss Powder Coat Finish            |                  |                  |                                  |
| <b>Decking</b>                     | 2" Pressure Treated Pine                 |                  |                  |                                  |
| <b>Dovetail</b>                    | Diamond Plate Knife Edge                 |                  |                  |                                  |
| <b>Ramp Style</b>                  | None                                     |                  |                  |                                  |
| <b>Ramp Length x Width</b>         | -  |                  |                  |                                  |
| <b>Ramp Load Cap. (lb./ea.)</b>    | -  |                  |                  |                                  |
| <b>Length (Overall/Deck)</b>       | 26'-10" / 21'-1"                         | 28'-10" / 23'-1" | 28'-10" / 23'-1" | 30'-10" / 25'-1"                 |
| <b>Width (Overall/Btw Fenders)</b> | 102" / 82"                               | 102" / 82"       | 102" / 82"       | 102" / 82"                       |
| <b>Stationary Deck Width</b>       | 80"                                      | 80"              | 80"              | 80"                              |
| <b>Tilting Deck Width</b>          | 73-3/4"                                  | 73-3/4"          | 73-3/4"          | 73-3/4"                          |
| <b>Height (Overall/Deck)</b>       | 35" / 22"                                | 35" / 22"        | 35" / 22"        | 35" / 22"                        |
| <b>Tilt Angle</b>                  | 14.5 Degree                              |                  |                  | 13 Degree                        |

#### Additional Features

- Extended (72") Tongue
- HD Bulkhead with Integrated Tie-Down Points
- Sealed Wiring Harness
- Welded Rear Board Retainers
- 4 1/2" Oversized 1/4" Thick Stake Pockets
- (4) 3/4" D-Rings
- Banjo Tie Downs in Dovetail
- Spare Tire Mount
- Integrated Oversized Toolbox
- Self-Triggering Interior Light and Battery Storage
- Recessed High-Visibility Rear Marker Lights
- Hydraulic Cushion Load Cylinder
- Cylinder Shut-Off Valve
- Easy Locking Tilt Bed Latch
- Balanced Gravity Tilt
- Limited 3-Year Warranty